

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Panduit](#)
[JP131WP2-L20](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

A. System Overview

B. Copper Systems

C. Fiber Optic Systems

D. Power over Ethernet

E. Zone Cabling

F. Wireless

G. Outlets

H. Media Distribution

I. Physical Infrastructure Management

J. Overhead & Underfloor Routing

K. Surface Raceway

L. Cabinets, Racks & Cable Management

M. Grounding & Bonding

N. Industrial

O. Labeling & Identification

P. Cable Management Accessories

Q. Index



PHYSICAL INFRASTRUCTURE SYSTEMS



PATENTED

J-Pro™ Cable Support System

- Patented design provides complete horizontal and vertical 1" bend radius control that helps prevent degradation of cable performance
- UL 2043 and CAN/ULC S102.2 listed and suitable for use in air handling spaces
- Pre-ripped assemblies allow for attachment to walls, ceilings, beams, threaded rods, drop wires and underfloor supports to meet requirements of a variety of applications
- Wide cable support base prevents pinch points that could cause damage to cables
- Cable tie channel allows user to easily install 3/4" (19.1mm) Tak-Ty® Cable Ties to retain cable bundle
- Durable non-metallic J Hook materials provide the ability to manage and support a large number of cables
- Material: Black Nylon 6.6 J Hook with metal attachments



JP2W-L20



JP2WP2-L20



JP2CM-L20



JP2DW-L20

| Part Number | Part Description | Max. Bundle Capacity | | Max. Cable Capacity | | | Std. Pkg. Qty. |
|--|---|----------------------|-------|---------------------|----------------|-----------------|----------------|
| | | In. | mm | Cat 6A (0.300") | Cat 6 (0.240") | Cat 5e (0.225") | |
| Wall Mount | | | | | | | |
| JP75W-L20 | J Hook for wall mount applications. One 1/4" (M6) mounting hole for user supplied screw. Not for use with powder actuated fasteners. | 0.75 | 19.0 | 5 | 8 | 10 | 50 |
| JP131W-L20 | | 1.31 | 33.3 | 15 | 25 | 29 | 50 |
| JP2W-L20 | | 2.00 | 50.8 | 30 | 46 | 55 | 50 |
| JP4W-X20 | | 4.00 | 101.6 | 115 | 180 | 200 | 10 |
| Wall Mount with Bracket | | | | | | | |
| JP75WP2-L20 | J Hook for powder actuated installation on walls. One 5/32" (M4) mounting hole and one 1/4" (M6) mounting hole for user supplied fasteners. | 0.75 | 19.0 | 5 | 8 | 10 | 50 |
| JP131WP2-L20 | | 1.31 | 33.3 | 15 | 25 | 29 | 50 |
| JP2WP2-L20 | | 2.00 | 50.8 | 30 | 46 | 55 | 50 |
| JP4WP2-X20 | | 4.00 | 101.6 | 115 | 180 | 200 | 10 |
| Ceiling Mount | | | | | | | |
| JP75CM-L20 | J Hook with ceiling mount bracket that has one 3/16" (M5), 1/4" (M6), and 3/8" (M10) mounting hole. | 0.75 | 19.0 | 5 | 8 | 10 | 50 |
| JP131CM-L20 | | 1.31 | 33.3 | 15 | 25 | 29 | 50 |
| JP2CM-L20 | | 2.00 | 50.8 | 30 | 46 | 55 | 50 |
| JP4CM-X20 | | 4.00 | 101.6 | 115 | 180 | 200 | 10 |
| Drop Wire and Threaded Rod Clip | | | | | | | |
| JP75DW-L20 | J Hook with clip for use with #12 wire, threaded rod up to 3/8" (9.5mm) in diameter. | 0.75 | 19.0 | 5 | 8 | 10 | 50 |
| JP131DW-L20 | | 1.31 | 33.3 | 15 | 25 | 29 | 50 |
| JP2DW-L20 | | 2.00 | 50.8 | 30 | 46 | 55 | 50 |

Suitable for use in air handling spaces in accordance with Sec. 300-22(c) and (d) of the National Electrical Code. JP4 family of parts suitable for use in single unit configurations. Listed in accordance with CAN/ULC S102.2 when mounted as single units or in pairs. Minimum spacing of 4 feet (1220mm) required between mount points. (Flame spread rating = 0, Smoke developed classification = 30). All dimensions represent typical outer cable diameter in inches (mm).

J-Pro™ Cable Support System (continued)



JP2SBC50-L20



JP2SBC50R-L20



JP2SBC87-L20



JP2SBC87R-L20



JP2HBC25R-L20

JP2HBC50R-L20

JP2HBC75R-L20

| Part Number | Part Description | Max. Bundle Capacity | | Max. Cable Capacity | | | Std. Pkg. Qty. |
|------------------------------|--|----------------------|-------|---------------------|----------------|-----------------|----------------|
| | | In. | mm | Cat 6A (0.300") | Cat 6 (0.240") | Cat 5e (0.225") | |
| Screw-On Beam Clamps | | | | | | | |
| JP75SBC50-L20 | J Hook with screw-on beam clamp for use with flanges up to 1/2" (12.7mm) thick. Non-rotating mount. | 0.75 | 19.0 | 5 | 8 | 10 | 50 |
| JP131SBC50-L20 | J Hook with screw-on beam clamp for use with flanges up to 1/2" (12.7mm) thick. Non-rotating mount. | 1.31 | 33.3 | 15 | 25 | 29 | 50 |
| JP2SBC50-L20 | J Hook with screw-on beam clamp for use with flanges up to 1/2" (12.7mm) thick. Non-rotating mount. | 2.00 | 50.8 | 30 | 46 | 55 | 50 |
| JP4SBC50-X20 | J Hook with screw-on beam clamp for use with flanges up to 1/2" (12.7mm) thick. Non-rotating mount. | 4.00 | 101.6 | 115 | 180 | 200 | 10 |
| JP75SBC50R-L20 | J Hook with screw-on beam clamp for use with flanges up to 1/2" (12.7mm) thick. Rotates 360 degrees. | 0.75 | 19.0 | 5 | 8 | 10 | 50 |
| JP131SBC50R-L20 | J Hook with screw-on beam clamp for use with flanges up to 1/2" (12.7mm) thick. Rotates 360 degrees. | 1.31 | 33.3 | 15 | 25 | 29 | 50 |
| JP2SBC50R-L20 | J Hook with screw-on beam clamp for use with flanges up to 1/2" (12.7mm) thick. Rotates 360 degrees. | 2.00 | 50.8 | 30 | 46 | 55 | 50 |
| JP4SBC50R-X20 | J Hook with screw-on beam clamp for use with flanges up to 1/2" (12.7mm) thick. Rotates 360 degrees. | 4.00 | 101.6 | 115 | 180 | 200 | 10 |
| JP75SBC87-L20 | J Hook with screw-on beam clamp for use with flanges up to 3/4" (19.1mm) thick. Non-rotating mount. | 0.75 | 19.0 | 5 | 8 | 10 | 50 |
| JP131SBC87-L20 | J Hook with screw-on beam clamp for use with flanges up to 3/4" (19.1mm) thick. Non-rotating mount. | 1.31 | 33.3 | 15 | 25 | 29 | 50 |
| JP2SBC87-L20 | J Hook with screw-on beam clamp for use with flanges up to 3/4" (19.1mm) thick. Non-rotating mount. | 2.00 | 50.8 | 30 | 46 | 55 | 50 |
| JP4SBC87-X20 | J Hook with screw-on beam clamp for use with flanges up to 3/4" (19.1mm) thick. Non-rotating mount. | 4.00 | 101.6 | 115 | 180 | 200 | 10 |
| JP75SBC87R-L20 | J Hook with screw-on beam clamp for use with flanges up to 3/4" (19.1mm) thick. Rotates 360 degrees. | 0.75 | 19.0 | 5 | 8 | 10 | 50 |
| JP131SBC87R-L20 | J Hook with screw-on beam clamp for use with flanges up to 3/4" (19.1mm) thick. Rotates 360 degrees. | 1.31 | 33.3 | 15 | 25 | 29 | 50 |
| JP2SBC87R-L20 | J Hook with screw-on beam clamp for use with flanges up to 3/4" (19.1mm) thick. Rotates 360 degrees. | 2.00 | 50.8 | 30 | 46 | 55 | 50 |
| JP4SBC87R-X20 | J Hook with screw-on beam clamp for use with flanges up to 3/4" (19.1mm) thick. Rotates 360 degrees. | 4.00 | 101.6 | 115 | 180 | 200 | 10 |
| Hammer-On Beam Clamps | | | | | | | |
| JP75HBC25R-L20 | J Hook with hammer-on beam clamp for use with flanges 1/8" – 1/4" (3.2mm – 6.4mm) thick. Rotates 360 degrees. | 0.75 | 19.0 | 5 | 8 | 10 | 50 |
| JP131HBC25R-L20 | J Hook with hammer-on beam clamp for use with flanges 1/8" – 1/4" (3.2mm – 6.4mm) thick. Rotates 360 degrees. | 1.31 | 33.3 | 15 | 25 | 29 | 50 |
| JP2HBC25R-L20 | J Hook with hammer-on beam clamp for use with flanges 1/8" – 1/4" (3.2mm – 6.4mm) thick. Rotates 360 degrees. | 2.00 | 50.8 | 30 | 46 | 55 | 50 |
| JP4HBC25R-X20 | J Hook with hammer-on beam clamp for use with flanges 1/8" – 1/4" (3.2mm – 6.4mm) thick. Rotates 360 degrees. | 4.00 | 101.6 | 115 | 180 | 200 | 10 |
| JP75HBC50R-L20 | J Hook with hammer-on beam clamp for use with flanges 5/16" – 1/2" (7.9mm – 12.7mm) thick. Rotates 360 degrees. | 0.75 | 19.0 | 5 | 8 | 10 | 50 |
| JP131HBC50R-L20 | J Hook with hammer-on beam clamp for use with flanges 5/16" – 1/2" (7.9mm – 12.7mm) thick. Rotates 360 degrees. | 1.31 | 33.3 | 15 | 25 | 29 | 50 |
| JP2HBC50R-L20 | J Hook with hammer-on beam clamp for use with flanges 5/16" – 1/2" (7.9mm – 12.7mm) thick. Rotates 360 degrees. | 2.00 | 50.8 | 30 | 46 | 55 | 50 |
| JP4HBC50R-X20 | J Hook with hammer-on beam clamp for use with flanges 5/16" – 1/2" (7.9mm – 12.7mm) thick. Rotates 360 degrees. | 4.00 | 101.6 | 115 | 180 | 200 | 10 |
| JP75HBC75R-L20 | J Hook with hammer-on beam clamp for use with flanges 9/16" – 3/4" (14.3mm – 19.1mm) thick. Rotates 360 degrees. | 0.75 | 19.0 | 5 | 8 | 10 | 50 |
| JP131HBC75R-L20 | J Hook with hammer-on beam clamp for use with flanges 9/16" – 3/4" (14.3mm – 19.1mm) thick. Rotates 360 degrees. | 1.31 | 33.3 | 15 | 25 | 29 | 50 |
| JP2HBC75R-L20 | J Hook with hammer-on beam clamp for use with flanges 9/16" – 3/4" (14.3mm – 19.1mm) thick. Rotates 360 degrees. | 2.00 | 50.8 | 30 | 46 | 55 | 50 |
| JP4HBC75R-X20 | J Hook with hammer-on beam clamp for use with flanges 9/16" – 3/4" (14.3mm – 19.1mm) thick. Rotates 360 degrees. | 4.00 | 101.6 | 115 | 180 | 200 | 10 |

Suitable for use in air handling spaces in accordance with Sec. 300-22(c) and (d) of the National Electrical Code. JP4 family of parts suitable for use in single unit configurations. Listed in accordance with CAN/ULC S102.2 when mounted as single units or in pairs. Minimum spacing of 4 feet (1220mm) required between mount points. (Flame spread rating = 0, Smoke developed classification = 30). All dimensions represent typical outer cable diameter in inches (mm).

Table continues on page L.68

- A. System Overview
- B. Copper Systems
- C. Fiber Optic Systems
- D. Power over Ethernet
- E. Zone Cabling
- F. Wireless
- G. Outlets
- H. Media Distribution
- I. Physical Infrastructure Management
- J. Overhead & Underfloor Routing
- K. Surface Raceway
- L. Cabinets, Racks & Cable Management
- M. Grounding & Bonding
- N. Industrial
- O. Labeling & Identification
- P. Cable Management Accessories
- Q. Index

A. System Overview

B. Copper Systems

C. Fiber Optic Systems

D. Power over Ethernet

E. Zone Cabling

F. Wireless

G. Outlets

H. Media Distribution

I. Physical Infrastructure Management

J. Overhead & Underfloor Routing

K. Surface Raceway

L. Cabinets, Racks & Cable Management

M. Grounding & Bonding

N. Industrial

O. Labeling & Identification

P. Cable Management Accessories

Q. Index

PANDUIT® PHYSICAL INFRASTRUCTURE SYSTEMS

J-Pro™ Cable Support System (continued)



JP2ZP-L20



JP2CP-L20



JP2UF100-L20

| Part Number | Part Description | Max. Bundle Capacity | | Max. Cable Capacity | | | Std. Pkg. Qty. |
|--|--|----------------------|-------|---------------------|----------------|-----------------|----------------|
| | | In. | mm | Cat 6A (0.300") | Cat 6 (0.240") | Cat 5e (0.225") | |
| Z-Purlin Clips | | | | | | | |
| JP75ZP-L20 | J Hook with z-purlin clip for use with angled flanges up to 1/4" (6.4mm) thick. | 0.75 | 19.0 | 5 | 8 | 10 | 50 |
| JP131ZP-L20 | | 1.31 | 33.3 | 15 | 25 | 29 | 50 |
| JP2ZP-L20 | | 2.00 | 50.8 | 30 | 46 | 55 | 50 |
| JP4ZP-X20 | | 4.00 | 101.6 | 115 | 180 | 200 | 10 |
| C-Purlin Clips | | | | | | | |
| JP75CP-L20 | J Hook with c-purlin clip for use with vertical flanges up to 1/4" (6.4mm) thick. | 0.75 | 19.0 | 5 | 8 | 10 | 50 |
| JP131CP-L20 | | 1.31 | 33.3 | 15 | 25 | 29 | 50 |
| JP2CP-L20 | | 2.00 | 50.8 | 30 | 46 | 55 | 50 |
| JP4CP-X20 | | 4.00 | 101.6 | 115 | 180 | 200 | 10 |
| Underfloor Pedestal Support Clamp | | | | | | | |
| JP75UF100-L20 | J Hook with underfloor clamp for use with pedestal support 7/8" square or 1 1/8" – 1 3/8" in diameter. | 0.75 | 19.0 | 5 | 8 | 10 | 50 |
| JP131UF100-L20 | | 1.31 | 33.3 | 15 | 25 | 29 | 50 |
| JP2UF100-L20 | | 2.00 | 50.8 | 30 | 46 | 55 | 50 |
| JP4UF100-X20 | | 4.00 | 101.6 | 115 | 180 | 200 | 10 |

Suitable for use in air handling spaces in accordance with Sec. 300-22(c) and (d) of the National Electrical Code. JP4 family of parts suitable for use in single unit configurations. Listed in accordance with CAN/ULC S102.2 when mounted as single units or in pairs. Minimum spacing of 4 feet (1220mm) required between mount points. (Flame spread rating = 0, Smoke developed classification = 30). All dimensions represent typical outer cable diameter in inches (mm).