

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Desco](#)
[39508](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Features

- Efficient means of shipping or storing ESD sensitive circuit boards and other items in accordance with ANSI/ESD S20.20 & ANSI/ESD S541
- Conductive crosslink black polyethylene cushion grade foam (3/8" thick, $R_v < 10^4$ ohms) laminated to top, and conductive crosslink black polyethylene pin insertion grade foam (1/4" thick, $R_v < 10^4$ ohms) in bottom (All dimensions are $\pm 1/16$ ")
- Impregnated corrugated static dissipative surface of 1×10^6 to $< 1 \times 10^9$ ohms per ANSI/ESD S11.1 and IEC 61340-2-3
- No assembly required
- Made in America

Item	Size I.D. - L x W x D (IN)
39508	2-1/2" x 1-1/4" x 1"
39536	3-7/16" x 2-1/8" x 1"
39542	3-3/4" x 3-3/4" x 1"
39550	7" x 3-1/2" x 1"

Note: These are inside Dimensions

Protektive Pak Impregnated Corrugated Specifications

Properties	Typical Values
Surface Resistance:	1×10^6 to $< 1 \times 10^9$ ohms
Static Shielding:	99.9% attenuation at 10kV; 99.6% attenuation at 30kV

Test Procedures/Method
ANSI/ESD S11.1
EIA 541, appendix E, capacitive probe test

Per Packaging standard ANSI/ESD section 6.2 Outside an EPA "Transportation of sensitive products outside of an EPA shall require packaging that provides:

1. Low charge generation.
2. Dissipative or conductive materials for intimate contact.
3. A structure that provides electrostatic discharge shielding."

Specifications and procedures subject to change without notice  Made in the United States of America

Small Component Shippers, Black Foam

PROTEKTIVE PAK
 13520 MONTE VISTA AVENUE, CHINO, CA 91710
 PHONE (909) 627-2578, FAX (909) 363-7331
ProtektivePak.com

DRAWING NUMBER
 39508

DATE:
 February
 2012