

Excellent Integrated System Limited


Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:


[Amphenol Pcd](#)
[SJE020026](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

REV	ECN	APP'D
A	5722	




WHITE MARKING
PER AW-2302



SCALE 1:1

NOTES:

- MATERIALS:**
 BODY: POLYETHERIMIDE PER MIL-P-46184.
 GROMMET: SILICONE BLEND ELASTOMER.
 DIODE: MIL-S-19500 (SEE TABLE)
 INTERNAL PIN CONTACT:
 COPPER ALLOY, HARD GOLD PLATE PER MIL-G-45204.
- PERFORMANCE SPECIFICATION PER MIL-T-81714.**
 (SUBJECT TO LIMITATIONS OF THE ELECTRONIC COMPONENTS)
 TEMPERATURE: -65°C TO 200°C.
 INSULATION RESISTANCE: 5000 MEGOHMS MIN AT 25°C.
 DIELECTRIC WITHSTANDING VOLTAGE:
 1500 VRMS AT SEA LEVEL,
 AND 200 VRMS AT 100,000 FT. ALTITUDE.
 CURRENT RATING: 7.5A FOR SIZE 20 CONTACTS.
 VIBRATION AND SHOCK: PER MIL-T-81714 PARA 3.5.8 & 9.
- MODULE ACCEPTS SOCKET CONTACTS (10) M39029/22-192.
- MODULE TO BE MOUNTED ON M81714/67 RAIL SYSTEM.



1.170 MAX

1.140 MAX



DATE CODE
.06 HIGH MARKING
COLOR: WHITE

DIMENSIONS	TOLERANCES	PROJECTION	Amphenol Pcd		TITLE			
ANSI Y14.5M UNITS: INCHES Pro/E FILE	.XX ±0.01 .XXX ±0.005 ANGLES ±10°		SPECIFICATION DRAWING		ELECTRONIC MODULE			
			DRWN	J. TON	01/17/02	511 OHM		
			ENGR	A. PATRIE	1-14-02	1/8 W		
			APPD	J. TON	1-14-02	SIZE	DWG NO.	REV
						A	SJE020026_C	A
						CODE: 58982	SCALE: 2:1	SHEET 1 OF 1

THIS DOCUMENT CONTAINS
PROPRIETARY INFORMATION WHICH
IS THE CONFIDENTIAL PROPERTY
OF AMPHENOL PCD, BEVERLY, MA