



## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ITT Cannon, LLC](#)  
[DDM50PDNMBK52](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



Datasheet for part number DDM50PDNMBK52

|   |
|---|
| Our Catalog Part Number: DDM-50P-D-NMBK52                             |
| Brand: Cannon Product Category: D Sub Product Line: D Sub Series: D*M |

|                                 |   |
|---------------------------------|---|
| Product Datasheet               |   |
| General                         | D*M High reliable D-Sub Connectors          |
| Wire Gauge Range AWG            | AWG 20-28                                   |
| Mating Cycles                   | 200   |
| Contact Arrangement             | 50 contacts size 20                         |
| Dielectric Withstanding Voltage | 1000 VAC at sea level                       |
| Current Rating                  | 7.5 A max                                   |
| Contact Resistance              | 7.5 milli Ohm max                           |
| Operating Temperature           | -55°/+125°                                  |
| Salt Spray Test                 | 20 hours                                    |
| Shell Material                  | steel                                       |
| Shell Finish                    | 50 microinch gold over 100 microinch copper |
| Insulator Material              | Thermoplastic, type PCT UL 94V-0            |
| Insulator Color                 | black                                       |
| Gender                          | Pin   |
| Contact Type                    | Right angled PCB                            |
| Contact Material                | copper alloy                                |
| Contact Finish                  | 50 microinch gold over 100 microinch copper |
| Hardware                        | .120" (3,05mm) Through Hole                 |