

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Cinch Connectivity Solutions](#)

[BJ74C-201](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

DASH NUMBER	CABLES ACCOMMODATED	A MAX	ASSEMBLY PER	DATA CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO TROMPETER ELECTRONICS INC. AND SHALL NOT BE DISCLOSED, COPIED OR REPRODUCED FOR PROMOTION OR MANUFACTURE WITHOUT EXPRESS WRITTEN PERMISSION.	REV	DESCRIPTIONS	DATE	APPROVED
-201	M17176-00002	.80	TAI-166	-301	GC875GCI, GRUMMAN	TA-168	6/17/09	WJL/EX
-202	TWC-78-1			-302	GC875GB1, GRUMMAN			
-203	TWC-124-1A			-303	5022E5111, RAYCHEM			
-204	10502, RAYCHEM			-304	7528A5314, RAYCHEM			
-205	TWAC-78-1F2			-305	M 71177-00001			
-206	7826DC13C, RAYCHEM			-306	295-3804 MICRODOT			
-207	83310 BELDEN			-307	TRC-75-2			
-208	202-3927, MICRODOT			-308	TRC-75-1			
-209	202-3942, MICRODOT			-309	TRC-50-1			
-210	845, BELDEN			1.55	TAI-138			
-211	202-3934, MICRODOT	-302	CPD221888, RAYCHEM					
-212	2524E0114, RAYCHEM	-303	2526D1114, RAYCHEM					
-213	TWC-78-2	-304	GC8753R1, GRUMMAN					
-214	TWC-124-2	-305	10613, RAYCHEM					
-215	BL-982 TIMES	-306	10613, RAYCHEM					
-216	BL-1242 TIMES	-307	11MS2-1149, HIGGINS					
-217	GC875TM24H, GRUMMAN	-308	TWCP-124-3					
-218	CPD221888, RAYCHEM	-309	PS665PL, PRIME STOCK					
-219	2526D1114, RAYCHEM	1.80	TAI-166			-301	GC875GCI, GRUMMAN	TAI-168
-220	GC8753R1, GRUMMAN			-302	GC875GB1, GRUMMAN			
-221	10613, RAYCHEM			-303	5022E5111, RAYCHEM			
-222	10613, RAYCHEM			-304	7528A5314, RAYCHEM			
-223	11MS2-1149, HIGGINS			-305	M 71177-00001			
-224	TWCP-124-3			-306	295-3804 MICRODOT			
-225	PS665PL, PRIME STOCK			-307	TRC-75-2			
-226	GC8753R1, GRUMMAN			-308	TRC-75-1			
-227	10613, RAYCHEM			-309	TRC-50-1			
-228	10613, RAYCHEM			1.55	TAI-138	-301	GC875TM24H, GRUMMAN	
-229	CPD221888, RAYCHEM	-302	CPD221888, RAYCHEM					
-230	2526D1114, RAYCHEM	-303	2526D1114, RAYCHEM					
-231	GC8753R1, GRUMMAN	-304	GC8753R1, GRUMMAN					
-232	10613, RAYCHEM	-305	10613, RAYCHEM					
-233	10613, RAYCHEM	-306	10613, RAYCHEM					
-234	11MS2-1149, HIGGINS	-307	11MS2-1149, HIGGINS					
-235	TWCP-124-3	-308	TWCP-124-3					
-236	PS665PL, PRIME STOCK	-309	PS665PL, PRIME STOCK					

  

5. EXAMPLE OF COMPLETE MODEL NUMBER:

BJ74C-201

BASIC MODEL NUMBER      CABLE GROUP DASH NUMBER

1. SHRINKABLE STRAIN RELIEF AND/OR SHRINKABLE SEALING SLEEVE SUPPLIED LOOSE AS FOLLOWS:

a. CABLE GROUPS -201 THROUGH -210, -217 THROUGH -303, -305, -307 AND -309

1 SHRINKABLE STRAIN RELIEF (1.00 LONG)  
 1 SHRINKABLE SEALING SLEEVE (1.25 LONG)

b. CABLE GROUPS -211 THROUGH -216, -224, -225, -306 AND -308

1 SHRINKABLE STRAIN RELIEF (1.75 LONG)

3. MAXIMUM PANEL THICKNESS: .140

2. CONDUCIVE INVAR/STAINLESS STEEL INSULATED TIGHT CRIMP BUSHING MOUNT CABLE RECEPTACLE

1. FINISH: IT'S-A-CRICKLE

NOTES: UNLESS OTHERWISE SPECIFIED.

Labels in drawing: .750 HEX NUT, .625-24UNCF-2A, SHRINKABLE STRAIN RELIEF (CLEAR 175° C), Ø.800, SHRINKABLE SEALING SLEEVE (LONG), .414 MIN, .416 ± .010, .030, MAX.

RECOMMENDED PANEL CUTOUT: Ø.635, .284, .28

RECOMMENDED HEX CRIMP: .344 HEX

-202 SHOWN  
**RED INDICATES ORIGINAL**

  

INTERPRET DRAWING PER MIL-STD-100, DIMENSIONS ARE IN INCHES AND INCLUDE FINISH THICKNESS UNLESS OTHERWISE SPECIFIED.	TOL: UNLESS SPECIFIED: .XX ± .02 .XXX ± .010 ANGLE = 1°	<p>a cinch connectivity solutions brand</p>
DATE: 5-26-09 DRAWN BY: M.J. CHECKED BY: M.J. APPROVED BY: M.J. 5/29/09	MATERIAL: FINISH:	TITLE: BJ74C SIZE: CAGE CODE A 14949 DRAWING NO: 3-0201 DATE: 11-11-86 SHEET: 1C