

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Knowles](#)

[EM-26734-D34](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

MATCHED PAIR
MICROPHONE

EM-26734-D34
SHEET 2.1

PAIR	CONSIST OF:
EM-26734-D34	(2) EM-26739-D34

BOTH MICROPHONES OF THE PAIR ARE TESTED TO EM-6739-D34 SHT 2.1 AND THEN MATCHED TO THE OTHER MICROPHONE USING THE SPECIFICATION AND CONDITIONS BELOW:

FREQUENCY	TEST TYPE	RANGE OF DEVIATION BETWEEN MICROPHONES	UNITS
1 kHz	SENSITIVITY	2.0 MAX.	dB
200 Hz	PHASE	1.5 MAX.	DEGREES
5000 Hz	PHASE	5.0 MAX.	DEGREES
7000 Hz	SENSITIVITY	1.0 MAX.	dB

NOTES:

1. DC SUPPLY VOLTAGE 1.1 VOLTS.
2. SENSITIVITY AND PHASE VALUES INDICATED ARE VALID AT 50% RH.

>>> SHOWS
MICROPHONE WITH THE
GREATER RESPONSE PHASE
VALUE AT 200 Hz.

