

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Weidmüller](#)
[1495060000](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



General ordering data

| | |
|------------------|--|
| Order No. | 1495060000 |
| Part designation | LPA SI STI3.2 OR |
| Version | PCB-component accessories, Fuse cartridge, System LP, No. of poles: 2, orange |
| EAN | 4008190095536 |
| Qty. | 50 pc(s). |

System parameters

| | |
|---|---------------------|
| Product family | System LP |
| Fitted to PCB | Soldered connection |
| Pitch | 10.16 mm |
| Pitch in inch | 0.4 inch |
| No. of poles | 2 |
| Fitted by customer | yes |
| Max. adjacent poles per row | 12 |
| No. of rows | 1 |
| Solder pin length | 3.2 mm |
| Dia. of fitting hole | 1.3 mm |
| Fitting hole tolerance | + 0.1 mm |
| No. of solder pins per pole | 2 |
| Electric shock protection to DIN VDE 0470 | IP 20 |

Material data

| | |
|---------------------------|---------------------|
| Insulating material | PA |
| Colour | orange |
| colour chart | Similar to RAL 2000 |
| Insulating material group | I |
| Flammability class UL 94 | V-2 |
| CTI | >= 600 |
| Contact base material | Copper alloy |
| Contact surface | tinned |
| Storage temperature, min. | -25 °C |
| Storage temperature, max. | 55 °C |

DIN IEC rating data

| | |
|--|-------|
| Rated current, min. No. pins (Tu=20°C) | 6.3 A |
| Rated voltage for overvoltage class/pollution severity II/2 | 500 V |
| Rated voltage for overvoltage class/pollution severity III/2 | 250 V |
| Rated voltage for overvoltage class/pollution severity III/3 | 250 V |

CSA rating data

| | |
|-----------------------------|-------|
| Rated voltage (Use group D) | 300 V |
| Rated current (Use group D) | 10 A |

UL 1059 rating data

| | |
|-----------------------------|-------|
| Rated voltage (Use group D) | 300 V |
| Rated current (Use group D) | 10 A |

Approvals

Approvals institutes



Classifications

| | |
|------------|----------|
| ETIM 2.0 | NK |
| ETIM 3.0 | EC001284 |
| eClass 4.1 | NK |
| eClass 5.0 | NK |
| eClass 5.1 | NK |

Similar products

| Order No. | Part designation | Version |
|------------|------------------|---|
| 1495160000 | LPA SI STI4.5 OR | PCB-component accessories, Fuse cartridge, System LP, No. of poles: 3, orange |