

Excellent Integrated System Limited


Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Weidmüller](#)
[1012900000](#)

For any questions, you can email us directly:

sales@integrated-circuit.com


General ordering data

Order No.	1012900000
Part designation	WTR 2.5/D/O.TNHE
Version	Disconnect and modular disconnect terminal, 2.5 mm ² , Screw connection, Wemid, dark beige, TS 35
EAN	4008190144623
Qty.	100 pc(s).

Product notes

Product description	Modular disconnect terminals enable circuits to be quickly isolated from the supply so that, for example, maintenance or repair work can be carried out.
Function	Without disconnect

2 clampable conductors (H05V/H07V) with equal cross-section (rated connection)

Solid, min.	0.5 mm ²
Solid, max.	1.5 mm ²
Flexible, min.	0.5 mm ²
Flexible, max.	1.5 mm ²
Flexible with ferrule, min. (DIN 46228 pt 1)	0.5 mm ²
Flexible with ferrule, max. (DIN 46228 pt 1)	1.5 mm ²

Additional technical data

Colour of insulating material	dark beige
Connection direction	on side
End plate required	Yes
Explosion-tested version "Ex e"	No
Installation advice	TS 35
Insulating material	Wemid
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1

Additional technical data

No. of terminal strips per level	2
Open sides	right
Operating temperature range	- 50 °C, + 120 °C
Product family	W-Series
Type of connection	Screwed
Type of mounting	Snap-on
Version	Test-disconnect terminals

CSA rating data

Voltage (CSA)	300 V
---------------	-------

Conductors for clamping (additional connection)

Flexible with ferrule, min. (DIN 46228 pt 1)	0.5 mm ²
Flexible with ferrule, max. (DIN 46228 pt 1)	2.5 mm ²

Conductors for clamping (rated connection)

Type of connection	Screw connection
2nd type of connection	screwed
Connection direction	on side
No. of connections	2
Tightening torque range	0.4...0.8 Nm
Torque level with DMS electric screwdriver	1
Solid, min.	0.5 mm ²
Solid, max.	4 mm ²
Stranded, min.	1.5 mm ²
Stranded, max.	4 mm ²
Flexible, min.	0.5 mm ²
Flexible, max.	4 mm ²
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm ²
Flexible with ferrule, max. (DIN 46228/1)	2.5 mm ²
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0.5 mm ²
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	2.5 mm ²
AWG conductor size, min.	AWG 30
AWG conductor size, max.	AWG 12
AWG conductor size, min.	0.05 mm ²
AWG conductor size, max.	3.31 mm ²

Dimensions

Length	60 mm
Weight	10 g
TS 35 offset	32 mm

Disconnect terminals

Torque level with DMS electric screwdriver	1
--	---

Rating data

Rated cross-section	2.5 mm ²
---------------------	---------------------

UL rating data

Voltage (UL) 300 V

Approvals

Approvals institutes



Classifications

ETIM 2.0	EC000902
ETIM 3.0	EC000902
eClass 4.1	27-14-11-17
eClass 5.0	27-14-11-26
eClass 5.1	27-14-11-26

Similar products

Order No.	Part designation	Version
1855610000	WTR 2.5	Disconnect and modular disconnect terminal, 2.5 mm ² , Screw connection, Wemid, beige, TS 35
1961750000	WTR 2.5 D+ 2STB 6.9/2.3	
1014700000	WTR 2.5 D 2STB 7.5/2.3	Disconnect and modular disconnect terminal, 2.5 mm ² , Screw connection, Wemid, dark beige, TS 35
1014600000	WTR 2.5 D 2STB 7.5/2.3	Disconnect and modular disconnect terminal, 2.5 mm ² , Screw connection, Wemid, dark beige, TS 35
1964810000	WTR 2.5 D- 2STB 6.9/2.3	
1011120000	WTR 2.5 GE	Disconnect and modular disconnect terminal, 2.5 mm ² , Screw connection, Wemid, yellow, TS 35
1011130000	WTR 2.5 GN	Disconnect and modular disconnect terminal, 2.5 mm ² , Screw connection, Wemid, green, TS 35
1011150000	WTR 2.5 GR	Disconnect and modular disconnect terminal, 2.5 mm ² , Screw connection, Wemid, grey, TS 35
1878530000	WTR 2.5 OR	Disconnect and modular disconnect terminal, 2.5 mm ² , Screw connection, Wemid, Orange, TS 35
1011140000	WTR 2.5 RT	Disconnect and modular disconnect terminal, 2.5 mm ² , Screw connection, Polyamide, red, TS 35
1013000000	WTR 2.5 STB2.0	Disconnect and modular disconnect terminal, 2.5 mm ² , Screw connection, Wemid, dark beige, TS 35
1011200000	WTR 2.5 STB2.3	Disconnect and modular disconnect terminal, 2.5 mm ² , Screw connection, Wemid, dark beige, TS 35
1011280000	WTR 2.5 STB2.3 BL	Disconnect and modular disconnect terminal, 2.5 mm ² , Screw connection, Wemid, blue/light blue, TS 35
1011220000	WTR 2.5 STB2.3 GE	Disconnect and modular disconnect terminal, 2.5 mm ² , Screw connection, Wemid, yellow, TS 35

1011240000	WTR 2.5 STB2.3 RT	Disconnect and modular disconnect terminal, 2.5 mm ² , Screw connection, Polyamide, red, TS 35
1011210000	WTR 2.5 STB2.3 SW	Disconnect and modular disconnect terminal, 2.5 mm ² , Screw connection, Polyamide, black, TS 35
1011110000	WTR 2.5 SW	Disconnect and modular disconnect terminal, 2.5 mm ² , Screw connection, Polyamide, black, TS 35
1013200000	WTR 2.5/D+ STB2.3	Disconnect and modular disconnect terminal, 2.5 mm ² , Screw connection, Wemid, dark beige, TS 35
1013600000	WTR 2.5/D-	Disconnect and modular disconnect terminal, 2.5 mm ² , Screw connection, Wemid, dark beige, TS 35
1013300000	WTR 2.5/D- STB2.3	Disconnect and modular disconnect terminal, 2.5 mm ² , Screw connection, Wemid, dark beige, TS 35
1013700000	WTR 2.5/D/DRBR	Disconnect and modular disconnect terminal, 2.5 mm ² , Screw connection, Wemid, dark beige, TS 35
1012800000	TR 2.5/O.TNHE STB2.3	Disconnect and modular disconnect terminal, 2.5 mm ² , Screw connection, Wemid, dark beige, TS 35
1039900000	WTR 2.5/ZZ	Disconnect and modular disconnect terminal, 2.5 mm ² , Screw connection, Wemid, dark beige, TS 35
1039980000	WTR 2.5/ZZ BL	Disconnect and modular disconnect terminal, 2.5 mm ² , Screw connection, Wemid, blue/light blue, TS 35
7910180000	WTR 4	Disconnect and modular disconnect terminal, 4 mm ² , Screw connection, Wemid, dark beige, TS 35
7910190000	WTR 4 BL	Disconnect and modular disconnect terminal, 4 mm ² , Screw connection, Wemid, blue, TS 35
7910210000	WTR 4 STB	Disconnect and modular disconnect terminal, 4 mm ² , Screw connection, Wemid, dark beige, TS 35
7910220000	WTR 4 STB BL	Disconnect and modular disconnect terminal, 4 mm ² , Screw connection, Wemid, blue, TS 35
1905080000	WTR 4/ZR	Disconnect and modular disconnect terminal, 4 mm ² , Screw connection, Wemid, dark beige
1905110000	WTR 4/ZR STB	Disconnect and modular disconnect terminal, 4 mm ² , Wemid, dark beige, TS 35
1905090000	WTR 4/ZZ	Disconnect and modular disconnect terminal, 4 mm ² , Screw connection, Wemid, dark beige
1905100000	WTR 4/ZZ STB	Disconnect and modular disconnect terminal, 4 mm ² , Wemid, dark beige, TS 35