

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Weidmüller](#)
[1676640000](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

General ordering data

Order No.	1676640000
Part designation	ZDUS
Version	Feed-through terminal, Shield feed-through terminal, Wemid, dark beige, Direct mounting
EAN	4008190462871
Qty.	20 pc(s).

Product notes

Product description	The shielding braid from the stripped control cables is soldered to the ZDUS or crimped on with 2.8 x 0.8 mm cable-lug sleeves. The ZDUS can be installed along side of the ZDU 2.5, ZDU 2.5/3 AN, ZDU 4, ZDU 6 and ZTR 2.5.
---------------------	--

Additional technical data

Colour of insulating material	dark beige
Connection direction	top
End plate required	Yes
Installation advice	Direct mounting
Insulating material	Wemid
No. of levels	1
Operating temperature range	- 50 °C, + 120 °C
Product family	Z-series
Type of connection	Crimping
UL 94 flammability rating of insulation material	V-0

Conductors for clamping (rated connection)

Type of connection	Shield feed-through terminal
Connection direction	top
Solid, min.	0.5 mm ²
Solid, max.	2.8 mm ²
Flexible, min.	0.5 mm ²
Flexible, max.	1.5 mm ²

Dimensions

Width	4.8 mm
Height of lowest version	33.5 mm
Length	83.5 mm

Approvals

Approvals institutes


Classifications

eClass 4.1	27-14-11-20
eClass 5.0	27-14-11-20
eClass 5.1	27-14-11-20

Classifications

Similar products

Order No.	Part designation	Version
-----------	------------------	---------