



**Distributor of ITT Cannon, LLC: Excellent Integrated System Limited**

Datasheet of CIR06CF-20-11P - CIR 13C 13#16 PIN PLUG

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ITT Cannon, LLC](#)

[CIR06CF-20-11P](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



Datasheet for part number CIR06CF-20-11P

|   |
|---|
| Our Catalog Part Number: CIR06CF-20-11P   |
| Brand: VEAM Product Category: Circular Product Line: Veam CIR, VBN, Other Series: CIR / FRCIR |

|  |  |
|--|--|
| Product Datasheet                                  |  |
| SERIES   | Connector with Bayonet Coupling  |
| Shell Style  | Straight Plug Connector  |
| Environmental Class                                | Backshell with C style clamp   |
| Shell Size   | 20   |
| Contact Arrangement                                | 20-11  |
| Total Number of contacts                           | 13 contacts  |
| Number of Contacts Size 16                         | 13 contacts size 16  |
| Gender   | Pin  |
| Contact Type                                       | Solder (standard class)  |
| Contact Plating                                    | Silver   |
| Shell Material                                     | Aluminium alloy  |
| Shell Plating                                      | Olive drab chromate over cadmium plating (conductive)  |
| Wire Size Cross Section for Contacts Size 16       | 1,0-1,5 mm <sup>2</sup> or AWG 18-16   |
| Contact Rating for Contacts Size 16                | Maximum Current = 22 A<br>Rated and Test Current = 13 A<br>Potential Drop max. 74 mV   |
| Shock Resistance                                   | Waterproof to 10 meters (33 ft)<br>12 h (14.7 PSI)   |
| Coupling   | 2000 couplings minimum   |
| Service Rating Letter                              | I  |
| Operating Voltage DC                               | 250 V  |
| Operating Voltage AC                               | 200 V  |
| Dielectric strength - Minimum Flashover AC RMS     | 1400 V   |
| Dielectric strength - Test Voltage AC RMS (Hi Pot) | 1000 V   |
| Note   | Voltages in excess of 30 V ac or 42.5 V dc are potentially hazardous and care should be taken to ensure that such voltages can't be transmitted in any way to exposed metal parts of the connector body. |
| General  | Veam CIR series Connectors are produced in accordance with NATO Standard VG95234, which is based on MIL-C-5015 for physical size, layout and environment requirements.                                   |