

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Triad Magnetics](#)
[F-226U](#)

For any questions, you can email us directly:
sales@integrated-circuit.com



POWER TRANSFORMER
Chassis Mount: Single Secondary

F-226U

Electrical Specifications (@25C)

1. Maximum Power: 288.0 VA
2. Primary: 115V 60 Hz
3. Secondary: 24.0VCT @ 12.0 Amps
4. Voltage Regulation: 5 % TYP @ full load to no load
5. Temperature Rise: 35C TYP (45C MAX allowed)

Description:

The F-226U is part of a series which has a long history of reliable service in the field, made from a proven design and constructed with UL recognized materials.

Construction:

Wound on a single channel nylon bobbin. Materials are UL recognized, Class B (130° C) rated.

Safety:

These products are 100% hipot tested with an insulation of 1500V between primary and secondary windings as well as between the primary / secondary windings and the core.


Dimensions: Units: In inches

A	B	C	D	E
4.562	3.750	4.125	3.00	3.250

Lead length: 7.0 inches ± 1 inch

Weight: 10.40 lbs

Schematic:



Primary: Black to Black
 Secondary: Green to Green

RoHS Compliance: As of manufacturing date February 2005, all standard products meet the requirements of 2011/65/EU, known as the RoHS initiative.

* Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics' website for the most current version.

