

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Tripp Lite](#)  
[IS1800HG](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

## Isolator Series 120V 1800W UL60601-1 Medical-Grade Isolation Transformer with 6 Hospital-Grade Outlets

MODEL NUMBER: IS1800HG



### Highlights

- Complete line isolation, noise filtering and surge suppression; ideal for sensitive equipment
- 1800 watts, 6 outlets, 10-ft. power cord
- Hospital-grade plug and receptacles
- Leakage current less than 100 microamps
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### Package Includes

- IS1800HG Isolation Transformer
- NEMA5-15P replacement plug
- User manual with warranty information

### Description

Isolator Series UL60601-1 Listed Medical Grade Isolation Transformers offer line isolation, continuous noise filtering and enhanced common mode surge suppression. An internal low-impedance isolation transformer component offers 100% isolation from the input AC line. Full UL60601-1 medical-grade listing with hospital-grade plug and outlet receptacles makes Isolator medical-grade transformers ideal for protection of sensitive electronic equipment in patient-care areas. Faraday shield reduces the cumulative leakage current of the Isolator and connected equipment to levels less than 100 microamps. Secondary neutral-to-ground bonding virtually eliminates common mode noise, providing an isolated neutral-ground reference for sensitive equipment, and an inexpensive alternative to dedicated circuits and site electrical upgrades. Removes EMI/RFI noise, utility switching transients and harmonics generated by other on-site loads and utility or lightning related surge conditions. Active transformer filtering provides continuous common-mode noise rejection with no wearable parts. Unique ability to reduce surges in the worst of power environments to harmless levels. Reduces 6000V IEEE587 Cat A&B ring wave and combination wave test surges to only 0.5V common mode. Model IS1800HG includes 6 widely spaced NEMA 5-15R hospital-grade output receptacles, a 10-ft. power cord, hospital-grade input plug, circuit breaker overload protection, and lighted power switch. Rugged all-metal unit housing; ships ready for placement in any industrial, medical, office or network environment. PLUG/OUTLETS: Input - NEMA 5-20P Hospital Grade; Output - 6 NEMA 5-20R Hospital Grade ELECTRICAL: 120V AC, 60Hz, 2.1A (Requires NEMA 5-15R wall receptacle)

### Features

- The IS1800HG Medical Grade Isolation Transformer offers line isolation and continuous noise filtering
- Internal low-impedance isolation transformer with Faraday shield offers 100% isolation from the input AC line
- Full UL60601-1 medical-grade listing with hospital-grade plug and outlet receptacles makes Isolator Hospital Grade transformers ideal for the protection of sensitive electronic equipment in patient-care areas.
- Reduces the cumulative leakage current of the Isolator and connected equipment to levels less than 100 microamps. Secondary neutral to ground bonding eliminates common mode noise, providing an isolated ground reference for sensitive equipment
- Serves as an inexpensive alternative to dedicated circuits and site electrical upgrades
- Removes EMI/RFI noise, utility switching transients, load-generated harmonics and ground loops
- Active transformer filtering offers continuous common-mode noise rejection with no wearable parts; unique ability to reduce surges in the worst of power environments to harmless levels



**Tripp Lite**  
 1111 W. 35th Street  
 Chicago, IL 60609 USA  
 Telephone: 773.869.1234  
 www.tripplite.com

- Reduces 6000V IEEE587 Cat A&B ring wave and combination wave test surges to only 0.5V common mode
- Includes 6 widely spaced NEMA5-20R hospital-grade output receptacles, a 10-ft. power cord, hospital-grade input plug, circuit breaker overload protection, and lighted power switch
- Ships with NEMA5-20P input plug installed, package includes NEMA5-15P user-installable hospital-grade replacement plug for compatibility with common 15A wall receptacles
- Rugged all-metal unit housing; ships ready for upright tower placement in any industrial, medical, office or network environment

## Specifications

| OVERVIEW                               |  |
|--|--|
| Efficiency                             | 96%  |
| Let-through Voltage (Combination Wave) | L-N: 250V L-G: 250V N-G: 0.5V  |
| Let-through Voltage (Ring Wave)        | L-N: 20V L-G: 20V N-G: 0.5V  |
| Nominal Voltage / Frequency            | 120V / 60Hz  |
| Over Current Protection                | 1x thermal, 2 pole, 10 amp   |
| Shipping Weight                        | 58.00 lbs. / 26.31 kg  |
| Suppression Joule Rating               | 1190 (1020 input / 170 output)   |
| Surge Test Conditions                  | Per ANSI/IEEE C62.41 - IEEE587 Cat. A & B test waveforms                   |
| Total Harmonic Distortion              | Less than 1%   |
| VA / Watt Capacity                     | 1800   |
| Transformer Type                       | Hospital Grade, low impedance transformer-based line isolation transformer |
| OUTPUT                                 |  |
| Output Receptacles                     | (6) 5-20R-HG   |
| Output Amp Capacity                    | 15   |
| INPUT                                  |  |
| Input Cord Length (ft.)                | 10   |
| Input Cord Length (m)                  | 3.05   |
| Input Plug Type                        | NEMA 5-20P-HG  |
| SURGE / NOISE SUPPRESSION              |  |
| Noise Suppression Rating               | 35-65 DB   |
| ISOLATION                              |  |
| Leakage Current                        | Less than 100 microamps  |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

| <b>PHYSICAL</b>                     |                         |
|-------------------------------------|-------------------------|
| Unit Dimensions (hwd / in.)         | 7.75 x 8.25 x 12.25     |
| Unit Dimensions (hwd / cm)          | 19.69 x 20.96 x 31.11   |
| Cooling Method                      | Convection              |
| Form Factors Supported              | Tower                   |
| <b>CERTIFICATIONS</b>               |                         |
| Certifications                      | Tested to UL60601-1     |
| <b>WARRANTY</b>                     |                         |
| Product Warranty Period (Worldwide) | 2-year limited warranty |

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <http://www.tripplite.com/products/product-certification-agencies>