

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Global Power Technologies Group](#)  
[GDP24P060B](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



# GlobalPower

SiC Devices

## 600V SiC Schottky Diode



### GDP24P060B

|                                       |       |
|---------------------------------------|-------|
| VDC                                   | 600 V |
| Q <sub>C</sub>                        | 50 nC |
| I <sub>F</sub> (V <sub>F</sub> =1.5V) | 24 A  |

#### Amp+™ Features


- High surge current capable
- Zero reverse recovery current
- High bandwidth
- Fast, temperature-independent switching

#### Amp+™ Benefits

- Unipolar rectifier
- Zero switching loss
- Higher efficiency
- Smaller heat sink
- Parallel devices with thermal stability

#### Amp+™ Applications

- Motor drives
- Switch mode power supplies
- Power factor correction
- Diode snubber



| Part #     | Package  | Marking   |
|------------|----------|-----------|
| GDP24P060B | TO-247-2 | GDP24P060 |



| Maximum Rating                                     | Symbol                                | Conditions                                     | Value     | Unit             |
|----------------------------------------------------|---------------------------------------|------------------------------------------------|-----------|------------------|
| Continuous forward current                         | I <sub>F</sub>                        | T <sub>C</sub> =25 °C, T <sub>J</sub> =175 °C  | 46        | A                |
|                                                    |                                       | T <sub>C</sub> =125 °C, T <sub>J</sub> =175 °C | 25        |                  |
|                                                    |                                       | T <sub>C</sub> =150 °C, T <sub>J</sub> =175 °C | 17        |                  |
| Surge non-repetitive forward current sine halfwave | I <sub>F,SM</sub>                     | T <sub>C</sub> =25 °C, t <sub>p</sub> =8.3 ms  | 192       | A                |
|                                                    |                                       | T <sub>C</sub> =150 °C, t <sub>p</sub> =8.3 ms | 120       |                  |
| Non-repetitive peak forward current                | I <sub>F,max</sub>                    | T <sub>C</sub> =25 °C, t <sub>p</sub> =10 μs   | 480       | A                |
| i <sup>2</sup> t value                             | ∫i <sup>2</sup> dt                    | T <sub>C</sub> =25 °C, t <sub>p</sub> =8.3 ms  | 153       | A <sup>2</sup> s |
|                                                    |                                       | T <sub>C</sub> =150 °C, t <sub>p</sub> =8.3 ms | 60        |                  |
| Repetitive peak reverse voltage                    | V <sub>RRM</sub>                      | T <sub>J</sub> =25 °C                          | 600       | V                |
| Diode dv/dt ruggedness                             | dv/dt                                 | Turn-on slew rate, repetitive                  | 50        | V/ns             |
| Power dissipation                                  | P <sub>tot</sub>                      | T <sub>C</sub> =25 °C                          | 195       | W                |
| Operating & storage temperature                    | T <sub>C</sub> , T <sub>storage</sub> | Continuous                                     | -55...135 | °C               |
| Soldering temperature                              | T <sub>solder</sub>                   | Wave soldering leads                           | 260       | °C               |
| Mounting torque                                    |                                       | M3 Screw                                       | 1         | N-m              |

Electrical Characteristics, at T<sub>J</sub>=25 °C, unless otherwise specified

| Static Characteristics | Symbol          | Conditions                                   | Values |      |      | Unit |
|------------------------|-----------------|----------------------------------------------|--------|------|------|------|
|                        |                 |                                              | min.   | typ. | max. |      |
| DC blocking voltage    | V <sub>DC</sub> |                                              | 600    | -    | -    | V    |
| Diode forward voltage  | V <sub>F</sub>  | I <sub>F</sub> =24A, T <sub>J</sub> =25 °C   | -      | 1.5  | 1.7  |      |
|                        |                 | I <sub>F</sub> =24A, T <sub>J</sub> =175 °C  | -      | 2.5  | 2.8  |      |
| Reverse current        | I <sub>R</sub>  | V <sub>R</sub> =600V, T <sub>J</sub> =25 °C  | -      | 6.6  | 100  | μA   |
|                        |                 | V <sub>R</sub> =600V, T <sub>J</sub> =175 °C | -      | 2687 | -    |      |

## 600V SiC Schottky Diode

**Amp+™**

**GDP24P060B**

| Parameter | Symbol | Conditions | Values |      |      | Unit |
|-----------|--------|------------|--------|------|------|------|
|           |        |            | min.   | typ. | max. |      |

### AC Characteristics


|                         |          |                                            |   |     |     |    |
|-------------------------|----------|--------------------------------------------|---|-----|-----|----|
| Total capacitive charge | $Q_{rr}$ | $V_R=600V, T_j=27^\circ C$                 | - | 50  | -   | nC |
| Switching time          | $t_c$    | $di_F/dt=200 A/\mu s$<br>$T_j=150^\circ C$ | - | -   | <10 | ns |
| Total capacitance       | C        | $V_R=1 V, f=1 MHz$                         | - | 973 | -   | pF |
|                         |          | $V_R=300V, f=1 MHz$                        | - | 86  | -   |    |
|                         |          | $V_R=600V, f=1 MHz$                        | - | 83  | -   |    |

### Thermal Characteristics


|                                   |            |                        |   |      |   |              |
|-----------------------------------|------------|------------------------|---|------|---|--------------|
| Thermal resistance, junction-case | $R_{thJC}$ | Package (flange) mount | - | 0.77 | - | $^\circ C/W$ |
|-----------------------------------|------------|------------------------|---|------|---|--------------|

### Typical Performance


Forward Characteristics (parameterized on  $T_j$ )




Reverse Characteristics (parameterized on  $T_j$ )



Power Derating



Current Derating




# 600V SiC Schottky Diode


Amp+™

GDP24P060B

Capacitance




Recovery Charge



## Package Dimensions

### Package TO-247-2



**Note**

**RoHS Compliance**

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS2), as implemented March, 2013. RoHS Declarations for this product can be obtained from the Product Documentation sections of www.gptechgroup.com.

**REACH Compliance**

REACH substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, please contact our office at GPTG Headquarters in Lake Forest, California to insure you get the most up-to-date REACH SVHC Declaration. REACH banned substance information (REACH Article 67) is also available upon request.

This product has not been designed or tested for use in, and is not intended for use in, applications implanted into the human body nor in applications in which failure of the product could lead to death, personal injury or property damage, including but not limited to equipment used in the operation of nuclear facilities, life-support machines, cardiac defibrillators or similar emergency medical equipment, aircraft navigation or communication or control systems, or air traffic control.

Global Power Technologies Group Inc., Reserves the right to make changes to the product specifications and data in this document without notice.