

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Semtech](#)
[SCAS6](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

SEMTECH

STANDARD RECOVERY 1 PHASE FULL WAVE BRIDGE RECTIFIERS

SCAS05
SCAS1 SCAS2
SCAS4 SCAS6

January 16, 1998

TEL:805-498-2111 FAX:805-498-3804 WEB:http://www.semtech.com

STANDARD RECOVERY, HIGH CURRENT 1-PHASE FULL WAVE BRIDGE RECTIFIER ASSEMBLIES

- Low forward voltage drop
- Low reverse leakage current
- Aluminum case
- Low thermal impedance
- High forward and surge current ratings

QUICK REFERENCE DATA


- $V_R = 50V - 600V$
- $I_F = 70A$
- $I_R = 12.0\mu A$
- $I_{FSM} = 750A$

ABSOLUTE MAXIMUM RATINGS

Device Type	Working Reverse Voltage V_{RWM}	Average Rectified Current $I_{F(AV)}$						1 Cycle Surge Current $I_{FSM} t_p = 8.3mS$		Repetitive Surge Current I_{FRM}
		(@ case temperature)			(@ ambient temperature)			@ 25°C	@ 100°C	
		@ 55°C	@ 100°C	@ 125°C	@ 25°C	@ 55°C	@ 100°C			
Volts	Amps	Amps	Amps	Amps	Amps	Amps	Amps	Amps	Amps	
SCAS05	50	70	47	33	18	14	9	750	600	120
SCAS1	100									
SCAS2	200									
SCAS4	400									
SCAS6	600									

$$R_{\theta JC} = 0.4^{\circ}C/W$$

MECHANICAL



SEMTECH

**STANDARD RECOVERY
 1 PHASE FULL WAVE BRIDGE
 RECTIFIERS**

**SCAS05
 SCAS1 SCAS2
 SCAS4 SCAS6**

January 16, 1998

ELECTRICAL CHARACTERISTICS

Device Type	Maximum Reverse Leakage Current $I_R @ V_{RWM}$		Maximum Forward Voltage $V_F @ 18A/leg$	Reverse Recovery Time ¹ $t_{rr} @ 25^\circ C$	Maximum operating & storage temp. range. $T_{OP} T_{STG}$
	@ 25°C	@ 100°C			
	µA	µA	Volts	µS	°C
SCAS05 SCAS1 SCAS2 SCAS4 SCAS6	12.0	300	1.0	2.0	-55 to +150

¹ Measured on discrete devices prior to assembly




Fig 1. Forward voltage drop against output current per leg.




Fig 2. Transient thermal impedance characteristic per leg