Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

3M 8898-18MMX55M

For any questions, you can email us directly: sales@integrated-circuit.com



Distributor of 3M: Excellent Integrated System Limited

Datasheet of 8898-18MMX55M - BLU 18 MM X 55 M BULK

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Scotch[®] Strapping Tape 8898

3M

Technical Data	June, 2009
----------------	-------------------

T		n ,	
Prod	11Cf	Decer	ption
1100	uct		DUUL

Scotch® Strapping Tape 8898 is a general-purpose tape with a tensilized polypropylene film backing and pressure-sensitive synthetic adhesive. The tape is designed for a wide variety of industrial and packaging applications. Some typical applications include bundling, reinforcing, strapping, box closing, and appliance securing. The backing provides proper stiffness and excellent abrasion, moisture, and scuff resistance. The pressure-sensitive adhesive is specifically formulated to provide balanced adhesion to most fiberboard surfaces and a wide variety of plastic and metal surfaces. We suggest tests be completed to determine suitability particularly on surfaces other than those previously mentioned.

Construction	Backing	Adhesive	Colors	
	Tensilized polypropylene	Pressure-sensitive synthetic rubber resin	Blue, ivory	
Typical Physical Properties	Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.			
•			ASTM Test Method	
	Adhesion to Steel:	75 oz./in. width (82 N/100 mm width)	D-3330	
	Tensile Strength:	160 lbs./in.width (2800 N/100 mm width)	D-3759	
	Elongation at Break:	32%	D-3759	
	Tape Thickness:	4.6 mil (0.12 mm)	D-3652	
Available Sizes	Standard Widths:	.47 in. (12 mm), .71 in. (18 mm), .94 in. (24 mm), 1.9 in. (48 mm) and 2.8 in. (72 mm)		
		Blue only: 3.8 in. (96 mm)		
	Core Size (ID):	3 in. (76.2 mm)		
	Lengths:	60 yds. (55 m)		

Shelf Life

Storage Conditions

To obtain best performance, use this product within 18 months from date of manufacture.

Store behind present stock. Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40-50% relative humidity are recommended. Rotate your stock.



Distributor of 3M: Excellent Integrated System Limited

Datasheet of 8898-18MMX55M - BLU 18 MM X 55 M BULK

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Scotch® Strapping Tape

8898

Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001: 2000

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001: 2000 standards.





