

# Corrugated tube screw connection - HC-B-GCA-M20-PLRBK - 1412021

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



EVO corrugated pipe screw connection, size: M20, protection class: IP66, plastic



# **Key Commercial Data**

Packing unit	1 pc
Weight per Piece (excluding packing)	40.0 g
Custom tariff number	39269097
Country of origin	Poland

#### Technical data

#### General

corrugated pipe	Assembly instructions	Please observe the installation note provided for the WP-PA HF-HBBK corrugated pipe
-----------------	-----------------------	---

#### Ambient conditions

Ambient temperature (operation)	-40 °C 115 °C
Degree of protection	IP66

### Classifications

#### eCl@ss

eCl@ss 5.1	27143424
eCl@ss 6.0	27261207
eCl@ss 8.0	27449290
eCl@ss 9.0	27440290

#### **ETIM**

ETIM 4.0	EC000441





# Corrugated tube screw connection - HC-B-GCA-M20-PLRBK - 1412021


# Classifications

ETIM	
ETIM 5.0	EC000441
Approvals	
Approvals	
Approvals	
EAC	
Ex Approvals	
Approvals submitted	
Approval details	
EAC	

# Drawings







Dimensional drawing

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com