

## Excellent Integrated System Limited








Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Wurth Electronics Inc](#)  
[418121270802](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



**SPECIFICATION**

- >Contact Rating  
Switching : 25mA, 24VDC  
Non-Switching : 100mA, 50VDC
- >Contact Resistance  
Initial: 50mΩ max.  
After life test : 100mΩ max.
- >Insulation Resistance : min. 100MQ at 500VDC
- >Dielectric Strength : 500VAC for 1 minute
- >Operation Force : 600g max.
- >Mechanical Life : 2000 cycles
- >Electrical Life : 2000 cycles / 25mA, 24VDC
- >Raise Actuator type

**MATERIAL**

- >Cover : PA8T UL 94 V-0, color Black
- >Base : PA8T UL 94 V-0, color Black
- >Actuator : PA46 UL 94 V-0, color White
- >Contact : Gold Plated
- >Terminal : Gold Plated

**SOLDERING INFORMATION**

- >Terminal in SMD version
- >Reflow soldering according to JEDEC J-STD-020D Hot Air, 3 cycles max.
- >Keep in "off" position during soldering
- >For cleaning or washing only with top tape sealed
- >VPH Heating Process not recommended

**ENVIRONMENTAL**

- Storage condition : -40°C ~ +85°C
- Operation condition : -40°C ~ +85°C
- Compliance : Lead Free , ROHS , Reach

**PACKAGING INFORMATION**

- >Tape & Reel
- >On delivery in "off" position

DIMENSION					
No. of Poles	2	3	4	5	6
Dim. L (mm)	6.02	8.56	11.10	13.64	16.18
No. of Poles	7	8	9	10	12
Dim. L (mm)	18.72	21.26	23.80	26.34	31.42

Scale - 2:1

				<p>Würth Elektronik eiSos GmbH &amp; Co. KG EMC &amp; Inductive Solutions</p> <p>Max-Eyth-Str. 1 74638 Waldenburg Germany com. +49 79 42 945 - 0</p> <p>www.we-online.de eiSos@we-online.de</p>	<p>CREATED DaF</p> <p>CHECKED JLi</p> <p>GENERAL TOLERANCE DIN ISO 2768-1m</p> <p>PROJECTION METHOD </p> <p>SCALE 2 : 1</p>
				<p>DESCRIPTION</p> <p><b>WS-DIS</b> Raise actuator without top tape</p>	<p>TECHNICAL REFERENCE</p> <p>ORDER CODE</p> <p>4181212708xx</p>
REV.	FILE	DATE	BY	<p>SIZE IC type, SMD</p> <p>STATUS Released</p> <p>DATE 2015-12-11</p> <p>BUSINESS UNIT eiCan</p> <p>PAGE 1 / 1</p>	



This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. Würth Elektronik eiSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.