

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Tripp Lite](#)
[DB25-PAR](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

**Tripp Lite**

1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Network Surge Suppressor - Essential protection for data and communication lines

MODEL NUMBER: **DB25-PAR**

**Highlights**

- Complete serial port (DB25) surge protection
- Protects against the effects of electrostatic discharge, faulty wiring and lightning
- Lifetime product warranty
- Heavy duty grounding lead

Package Includes

- DB25-PAR dataline protector
- Instruction manual and warranty information

Description

Tripp Lite's DB25-PAR offers dataline surge suppression for many DB25 parallel ports. Protects pins 1-25 and D shell chassis for protection of parallel DB25 ports. User configurable for use with male or female captive DB25 ports. Convenient DB25 input and output connects directly to the protected port, obtaining a ground outlet from the computer chassis. Surge suppression is handled with balanced arrays of high-speed avalanche diodes that divert excess energies created by electrostatic discharges, faulty wiring or lightning away from network interface connections. Tripp Lite network surge suppressors reduce blown interface connections, garbled transmissions, system lock-ups and hard equipment failure by safely shunting dataline surges to ground. Lifetime warranty.

SUPPRESSION: Reversible DB25 m/f jacks, protects pins 1-25 and chassis, 7.5V clamping

Features

- DB25-PAR protects 25 pin parallel ports using DB25 connections
- Protects pins 1-25 and D shell chassis for protection of parallel applications.
- User configurable for use with male or female captive DB25 port
- Convenient DB25 input and output connects directly to the protected port, obtaining a ground outlet from the computer chassis
- Offers protection on all 25 data lines, plus D shell chassis
- Surge suppression utilizing high speed avalanche diodes divert excess energies on the network to ground
- Lifetime product warranty

Specifications

OUTPUT	
Circuit Breaker (amps)	750
INPUT	
Recommended Electrical Service	120V, 230V



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Input Connection Type	DB25
SURGE / NOISE SUPPRESSION	
Clamping Voltage (RMS)	7.5
DATALINE SURGE SUPPRESSION	
Telephone/DSL Protection	No
Cable (Coax) Protection	No
Additional Dataline Protection	1-25 & Chassis
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:
<http://www.tripplite.com/products/product-certification-agencies>