

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:


[Central Semiconductor Corp](#)
[P6KE15A TR](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

P6KE6.8A THRU P6KE440A
P6KE6.8CA THRU P6KE440CA

UNI-DIRECTIONAL
AND BI-DIRECTIONAL
SILICON TRANSIENT
VOLTAGE SUPPRESSORS
600 WATTS, 6.8 THRU 440 VOLTS



www.centrasemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR P6KE6.8A (Uni-Directional) and P6KE6.8CA (Bi-Directional) Series types are Transient Voltage Suppressors designed to protect voltage sensitive components from high voltage transients.

THIS DEVICE IS MANUFACTURED WITH A GLASS PASSIVATED CHIP FOR OPTIMUM RELIABILITY.

Note: For Uni-Directional devices add suffix "A" to part number. For Bi-Directional devices add suffix "CA" to part number.

MARKING: FULL PART NUMBER
Bi-directional devices shall not be marked with a Cathode band.

MAXIMUM RATINGS: (T_A=25°C unless otherwise noted)

Peak Power Dissipation (Note 1)
Steady State Power Dissipation (T_L=75°C)
Forward Surge Current (Uni-Directional only)
Operating and Storage Junction Temperature

| SYMBOL | | UNITS |
|-----------------------------------|-------------|-------|
| PPK | 600 | W |
| P _D | 5.0 | W |
| I _{FSM} | 100 | A |
| T _J , T _{stg} | -65 to +175 | °C |

ELECTRICAL CHARACTERISTICS: (T_A=25°C unless otherwise noted)

| TYPE | BREAKDOWN VOLTAGE | | | TEST CURRENT I _T mA | WORKING PEAK REVERSE VOLTAGE V _{RWM} V | MAXIMUM REVERSE LEAKAGE CURRENT I _R @ V _{RWM} µA | MAXIMUM CLAMPING VOLTAGE V _C @ I _{PP} V | PEAK PULSE CURRENT (Note 1) I _{PP} A | MAXIMUM TEMPERATURE COEFFICIENT θV _{BR} % / °C |
|---------|----------------------------------|-------|-------|--------------------------------------|---|--|---|---|---|
| | V _{BR} @ I _T | | | | | | | | |
| | MIN V | NOM V | MAX V | | | | | | |
| P6KE6.8 | 6.45 | 6.8 | 7.14 | 10 | 5.8 | 1000 | 10.5 | 57 | 0.057 |
| P6KE7.5 | 7.13 | 7.5 | 7.88 | 10 | 6.4 | 500 | 11.3 | 53 | 0.061 |
| P6KE8.2 | 7.79 | 8.2 | 8.61 | 10 | 7.02 | 200 | 12.1 | 50 | 0.065 |
| P6KE9.1 | 8.65 | 9.1 | 9.55 | 1.0 | 7.78 | 50 | 13.4 | 45 | 0.068 |
| P6KE10 | 9.5 | 10 | 10.5 | 1.0 | 8.55 | 10 | 14.5 | 41 | 0.073 |
| P6KE11 | 10.5 | 11 | 11.6 | 1.0 | 9.4 | 5.0 | 15.6 | 38 | 0.075 |
| P6KE12 | 11.4 | 12 | 12.6 | 1.0 | 10.2 | 5.0 | 16.7 | 36 | 0.078 |
| P6KE13 | 12.4 | 13 | 13.7 | 1.0 | 11.1 | 5.0 | 18.2 | 33 | 0.081 |
| P6KE15 | 14.3 | 15 | 15.8 | 1.0 | 12.8 | 5.0 | 21.2 | 28 | 0.084 |
| P6KE16 | 15.2 | 16 | 16.8 | 1.0 | 13.6 | 5.0 | 22.5 | 27 | 0.086 |
| P6KE18 | 17.1 | 18 | 18.9 | 1.0 | 15.3 | 5.0 | 25.2 | 24 | 0.088 |
| P6KE20 | 19.0 | 20 | 21.0 | 1.0 | 17.1 | 5.0 | 27.7 | 22 | 0.090 |
| P6KE22 | 20.9 | 22 | 23.1 | 1.0 | 18.8 | 5.0 | 30.6 | 20 | 0.092 |
| P6KE24 | 22.8 | 24 | 25.2 | 1.0 | 20.5 | 5.0 | 33.2 | 18 | 0.094 |
| P6KE27 | 25.7 | 27 | 28.4 | 1.0 | 23.1 | 5.0 | 37.5 | 16 | 0.096 |
| P6KE30 | 28.5 | 30 | 31.5 | 1.0 | 25.6 | 5.0 | 41.4 | 14.4 | 0.097 |
| P6KE33 | 31.4 | 33 | 34.7 | 1.0 | 28.2 | 5.0 | 45.7 | 13.2 | 0.098 |
| P6KE36 | 34.2 | 36 | 37.8 | 1.0 | 30.8 | 5.0 | 49.9 | 12 | 0.099 |
| P6KE39 | 37.1 | 39 | 41 | 1.0 | 33.3 | 5.0 | 53.9 | 11.2 | 0.100 |
| P6KE43 | 40.9 | 43 | 45.2 | 1.0 | 36.8 | 5.0 | 59.3 | 10.1 | 0.101 |

Notes: (1) Non-repetitive 10x1,000µs pulse.

R1 (8-September 2011)

**P6KE6.8A THRU P6KE440A
 P6KE6.8CA THRU P6KE440CA**


**UNI-DIRECTIONAL
 AND BI-DIRECTIONAL
 SILICON TRANSIENT
 VOLTAGE SUPPRESSORS
 600 WATTS, 6.8 THRU 440 VOLTS**



ELECTRICAL CHARACTERISTICS - Continued: ($T_A=25^\circ\text{C}$ unless otherwise noted)

| TYPE | BREAKDOWN VOLTAGE | | | TEST CURRENT I_T | WORKING PEAK REVERSE VOLTAGE V_{RWM} | MAXIMUM REVERSE LEAKAGE CURRENT $I_R @ V_{RWM}$ | MAXIMUM CLAMPING VOLTAGE $V_C @ I_{PP}$ | PEAK PULSE CURRENT (Note 1) I_{PP} | MAXIMUM TEMPERATURE COEFFICIENT θV_{BR} |
|---------|-------------------|-------|-------|-----------------------|---|--|--|---|--|
| | $V_{BR} @ I_T$ | | | | | | | | |
| | MIN V | NOM V | MAX V | mA | V | μA | V | A | % / $^\circ\text{C}$ |
| P6KE47 | 44.7 | 47 | 49.4 | 1.0 | 40.2 | 5.0 | 64.8 | 9.3 | 0.101 |
| P6KE51 | 48.5 | 51 | 53.6 | 1.0 | 43.6 | 5.0 | 70.1 | 8.6 | 0.102 |
| P6KE56 | 53.2 | 56 | 58.8 | 1.0 | 47.8 | 5.0 | 77 | 7.8 | 0.103 |
| P6KE62 | 58.9 | 62 | 65.1 | 1.0 | 53.0 | 5.0 | 85 | 7.1 | 0.104 |
| P6KE68 | 64.6 | 68 | 71.4 | 1.0 | 58.1 | 5.0 | 92 | 6.5 | 0.104 |
| P6KE75 | 71.3 | 75 | 78.8 | 1.0 | 64.1 | 5.0 | 103 | 5.8 | 0.105 |
| P6KE82 | 77.9 | 82 | 86.1 | 1.0 | 70.1 | 5.0 | 113 | 5.3 | 0.105 |
| P6KE91 | 86.5 | 91 | 95.5 | 1.0 | 77.8 | 5.0 | 125 | 4.8 | 0.106 |
| P6KE100 | 95.0 | 100 | 105 | 1.0 | 85.5 | 5.0 | 137 | 4.4 | 0.106 |
| P6KE110 | 104.5 | 110 | 115.5 | 1.0 | 94.0 | 5.0 | 152 | 4.0 | 0.107 |
| P6KE120 | 114 | 120 | 126 | 1.0 | 102 | 5.0 | 165 | 3.6 | 0.107 |
| P6KE130 | 123.5 | 130 | 136.5 | 1.0 | 111 | 5.0 | 179 | 3.3 | 0.107 |
| P6KE150 | 142.5 | 150 | 157.5 | 1.0 | 128 | 5.0 | 207 | 2.9 | 0.108 |
| P6KE160 | 152 | 160 | 168 | 1.0 | 136 | 5.0 | 219 | 2.7 | 0.108 |
| P6KE170 | 161.5 | 170 | 178.5 | 1.0 | 145 | 5.0 | 234 | 2.6 | 0.108 |
| P6KE180 | 171 | 180 | 189 | 1.0 | 154 | 5.0 | 246 | 2.4 | 0.108 |
| P6KE200 | 190 | 200 | 210 | 1.0 | 171 | 5.0 | 274 | 2.2 | 0.108 |
| P6KE220 | 209 | 220 | 231 | 1.0 | 185 | 5.0 | 328 | 2.0 | 0.108 |
| P6KE250 | 237.5 | 250 | 262.5 | 1.0 | 214 | 5.0 | 344 | 2.0 | 0.110 |
| P6KE300 | 285 | 300 | 315 | 1.0 | 256 | 5.0 | 414 | 2.0 | 0.110 |
| P6KE350 | 332.5 | 350 | 367.5 | 1.0 | 300 | 5.0 | 482 | 2.0 | 0.110 |
| P6KE400 | 380 | 400 | 420 | 1.0 | 342 | 5.0 | 548 | 2.0 | 0.110 |
| P6KE440 | 418 | 440 | 462 | 1.0 | 376 | 5.0 | 600 | 2.0 | 0.110 |

DO-15 CASE - MECHANICAL OUTLINE



| SYMBOL | DIMENSIONS | | | |
|--------|------------|-------|-------------|------|
| | INCHES | | MILLIMETERS | |
| | MIN | MAX | MIN | MAX |
| A | 0.028 | 0.034 | 0.71 | 0.86 |
| B | 0.230 | 0.300 | 5.84 | 7.62 |
| C | 0.104 | 0.140 | 2.64 | 3.56 |
| D | 1.000 | - | 25.40 | - |

DO-15 (REV: R1)

MARKING: FULL PART NUMBER
 Bi-directional devices shall not be marked with a Cathode band.

R1 (8-September 2011)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centrasemi.com

Worldwide Field Representatives:
www.centrasemi.com/wwreps

Worldwide Distributors:
www.centrasemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centrasemi.com/terms