Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:


Wurth Electronics Inc 74479899210

For any questions, you can email us directly: sales@integrated-circuit.com



Datasheet of 74479899210 - FIXED IND 1UH 2.3A 50 MOHM SMD

more than you expect




This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use.

Moreover Wilm Elektronic edsos Grind+ & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, shamarine, transportation (automotive control, train control, this control), transportation signal, disaster prevention, medical, public information network etc. Wirth Elektronic edsos Grind+ & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.


more than you expect



F1 Typical Inductance vs. Current Characteristics:



F2 Typical Temperature Rise vs. Current Characteristics:





its electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially expected or designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially expected or designed nor intended for use in execute an experiment of such usage before the design-in stage, in addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.






more than you expect



F3 Typical Inductance vs. Frequency Characteristics:



				Projection ————————————————————————————————————	WE-PMI Power Multilayer Inductor
				Würth Elektronik eiSos GmbH & C EMC & Inductive Solutions	
				Max-Eyth-Str. 1 74638 Waldenburg Germany	Order No. COMPLIANT SIZE
1.0	2014-11-10	SSt	MaKa	Tel. +49 (0) 79 42 945 - 0 www.we-online.com eiSos@we-online.com	74479899210 WORTH ELEKTRONIK A4
REV	DATE	BY	CHECKED	- cious@wc-utilite.cutt	Size: 1210

lact is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use.
nillator, acreapsace, availation, nuclear control, submarrier, bransportation (submorrier), transportation (submarrier), transportation (submarrier),




Datasheet of 74479899210 - FIXED IND 1UH 2.3A 50 MOHM SMD

more than you expect

H Soldering Specifications:



H1: Classification Reflow Profile for SMT components:



H2: Classification Reflow Profiles

Profile Feature	Pb-Free Assembly
Preheat - Temperature Min (T _{smin}) - Temperature Max (T _{smax}) - Time (t _s) from (T _{smin} to T _{smax})	150°C 200°C 60-120 seconds
Ramp-up rate (T _L to T _P)	3°C/ second max.
Liquidous temperature (T_L) Time (t_L) maintained above T_L	217°C 60-150 seconds
Peak package body temperature (T _p)	See Table H3
Time within 5°C of actual peak temperature (tp)	20-30 seconds
Ramp-down rate (T _P to T _L)	6°C/ second max.
Time 25°C to peak temperature	8 minutes max.

refer to IPC/JEDEC J-STD-020D

H3: Package Classification Reflow Temperature

	Package Thickness	Volume mm³ <350	Volume mm ³ 350 - 2000	Volume mm³ >2000
PB-Free Assembly	< 1.6 mm	260°C	260°C	260°C
PB-Free Assembly	1.6 - 2.5 mm	260°C	250°C	245°C
PB-Free Assembly	≥ 2.5 mm	250°C	245°C	245°C

refer to IPC/JEDEC J-STD-020D

				Projection ————————————————————————————————————		DESCRIPTION WE-PMI Power I	Multilayer Inductor			
				Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg		Order-No.				
1.0	2014-11-10	SSt	MaKa	Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com		74479899210	ROHS&REACH	SIZE A4		
REV	DATE	BY	CHECKED	eiSos@we-online.com		Size: 1210				

Inserted component has been designed and overlooped our usage or general excitorite output interview to product is not autournoor or team required our writer a large or on the product is resourced product or undergreated or the product is resourced product or team from the same and the product of the resource of the product of the pro



Datasheet of 74479899210 - FIXED IND 1UH 2.3A 50 MOHM SMD

more than you expect

I Cautions and Warnings:

The following conditions apply to all goods within the product series of WE-PMI of Würth Elektronik eiSos GmbH & Co. KG:

General

All recommendations according to the general technical specifications of the data sheet have to be complied with.

The usage and operation of the product within ambient conditions, which probably alloy or harm the wire isolation, has to be avoided.

If the product is potted in customer applications, the potting material might shrink during and after hardening. The product is exposed to the pressure of the potting material with the effect that the core, wire and termination is possibly damaged by this pressure and so the electrical as well as the mechanical characteristics are endangered to be affected. After the potting material is cured, the core, wire and termination of the product have to be checked if any reduced electrical or mechanical functions or destructions have occurred.

The responsibility for the applicability of customer specific products and use in a particular customer design is always within the authority of the customer. All technical specifications for standard products do also apply to customer specific products.

Cleaning agents that are used to clean the customer application might damage or change the characteristics of the component, body, pins or termination

Direct mechanical impact to the product shall be prevented as the core material could flake or in the worst case it could break.

Product specific:

Follow all instructions mentioned in the data sheet, especially:

- The soldering profile has to be complied with according to the technical reflow soldering specification, otherwise this will void the
 warranty.
- •All products shall be used before the end of the period of 12 months based on the product date code, if not a 100% solderability can't be ensured.
- Violation of the technical product specifications such as exceeding the nominal rated current will void the warranty.

The general and product specific cautions comply with the state of the scientific and technical knowledge and are believed to be accurate and reliable; however, no responsibility is assumed for inaccuracies or incompleteness.

				Projection ,		DESCRIPTION		
						WE-PMI Power Multilayer Inductor		
				Würth Elektronik eiSos Gmbl EMC & Inductive Solutions	H & Co. KG			
				Max-Eyth-Str. 1 74638 Waldenburg Germany		Order No.	COMPLIANT ROHS&REACH	SIZE
1.0	2014-11-10	SSt	MaKa	Tel. +49 (0) 79 42 945 - 0 www.we-online.com eiSos@we-online.com		74479899210	WÜRTH ELEKTRONIK	A4
REV	DATE	BY	CHECKED	elsos@we-online.com		Size: 1210	•	

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Wilm Elektronic Resides Genified X to XIS grounds are neither designed not intended for use in a reasonable, and a reliability standard in electronic experts, in a partie or intended to read a reliability standard in electronic specifically expected on experts and a reliability standard in electronic specifically governing such use. Moreover Wilm Elektronic Residual post and a reliability standard in electronic specifical post and reliability standard in electronic specifical post and reliability standard in electronic specifically governing such use. Moreover Wilm Elektronic specifical post and reliability standard in electronic specifically governing such use. Wilm Elektronic Residual post and reliability standard in electronic specifical post and reliability specifical post and reliability standard in electronic specifical post and reliability standard in electronic specifical post and reliability standard in electronic specifical post and reliability specifical post and reliability standard in electronic specifical post and reliability standard in electronic specifical post and reliability specifical post and reliab





Datasheet of 74479899210 - FIXED IND 1UH 2.3A 50 MOHM SMD

more than you expect

J Important Notes:

The following conditions apply to all goods within the product range of Würth Elektronik eiSos GmbH & Co. KG:

1. General Customer Responsibility

Some goods within the product range of Würth Elektronik eiSos GmbH & Co. KG contain statements regarding general suitability for certain application areas. These statements about suitability are based on our knowledge and experience of typical requirements concerning the areas, serve as general guidance and cannot be estimated as binding statements about the suitability for a customer application. The responsibility for the applicability and use in a particular customer design is always solely within the authority of the customer. Due to this fact it is up to the customer to evaluate, where appropriate to investigate and decide whether the device with the specific product characteristics described in the product specification is valid and suitable for the respective customer application or not.

2. Customer Responsibility related to Specific, in particular Safety-Relevant Applications
It has to be clearly pointed out that the possibility of a malfunction of electronic components or failure before the end of the usual lifetime cannot be completely eliminated in the current state of the art, even if the products are operated within the range of the specifications

In certain customer applications requiring a very high level of safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health it must be ensured by most advanced technological aid of suitable design of the customer application that no injury or damage is caused to third parties in the event of malfunction or failure of an electronic component.

Therefore, customer is cautioned to verify that data sheets are current before placing orders. The current data sheets can be downloaded at www.we-online.com.

3. Best Care and Attention

Any product-specific notes, cautions and warnings must be strictly observed. Any disregard will result in the loss of warranty,

4. Customer Support for Product Specifications

Some products within the product range may contain substances which are subject to restrictions in certain jurisdictions in order to serve spe cific technical requirements. Necessary information is available on request. In this case the field sales engineer or the internal sales person in charge should be contacted who will be happy to support in this matter

5. Product R&D

Due to constant product improvement product specifications may change from time to time. As a standard reporting procedure of the Product Change Notification (PCN) according to the JEDEC-Standard inform about minor and major changes. In case of further queries regarding the PCN, the field sales engineer or the internal sales person in charge should be contacted. The basic responsibility of the customer as per Section 1 and 2 remains unaffected



6. Product Life Cycle

Due to technical progress and economical evaluation we also reserve the right to discontinue production and delivery of products. As a standard reporting procedure of the Product Termination Notification (PTN) according to the JEDEC-Standard we will inform at an early stage about inevitable product discontinuance. According to this we cannot guarantee that all products within our product range will always be available. Therefore it needs to be verified with the field sales engineer or the internal sales person in charge about the current product availability expectancy before or when the product for application design-in disposal is considered.

The approach named above does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.

7. Property Rights
All the rights for contractual products produced by Würth Elektronik eiSos GmbH & Co. KG on the basis of ideas, development contracts as well as models or templates that are subject to copyright, patent or commercial protection supplied to the customer will remain with Würth Elektronik eiSos GmbH & Co. KG.

Würth Elektronik eiSos GmbH & Co. KG does not warrant or represent that any license, either expressed or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, application, or process in which Würth Elektronik eiSos GmbH & Co. KG components or services are used.

8. General Terms and Conditions

Unless otherwise agreed in individual contracts, all orders are subject to the current version of the "General Terms and Conditions of Würth Elektronik eiSos Group", last version available at www.we-online.com.

				Projection		DESCRIPTION			
				1					
				7		WE-PMI Power Multilayer Inductor			
				Würth Elektronik eiSos GmbH	& Co. KG				
				EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg					
						Order No.	COMPLIANT	SIZE	
				Germany Tel. +49 (0) 79 42 945 - 0		74470000040	ROHS&REACH		
1.0	2014-11-10	SSt	MaKa	www.we-online.com eiSos@we-online.com		74479899210 V WORTH ELEKTRONIK			
REV	DATE	BY	CHECKED	cious@we-utilite.cutt		Size: 1210			

ner safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use.

**Transportation (automotive control, train control, ship control), train profusion signal, disaster prevention, medical, public information network etc. . Wifird Evideronik eSos GmbH & Co KG must be informed about the intent of such usage before are high safety and reliability functions or performance. ectronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a high rew Withfl Electronik eSics Graft B. Co. KS products are neither designed nor intended for use in areas such as military, acrospace, aviation, nuclear control, subment sign in stage, in addinor, sufficient reliability evaluation herical for safety must be performed on every electronic component which is used in electrical circuits that req