

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[B B Battery](#)

[BP1.2-6-T1](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



VRLA Rechargeable Battery

BP1.2-6



FEATURES

- Maintenance free(no water topping-up required).
- No free acid(Non-spillable battery).
- Low self-discharge rate, lower than 3% capacity loss per month.
- Can be used in any orientation(excluding used inverted).
- Absorbent Glass Mat technology for efficient gas recombination.

APPLICATION

- UPS
- Security
- Medical
- Lojack



SPECIFICATIONS

Nominal Voltage	6 V
Nominal Capacity	1.2Ah @ 20 hour rate F.V.(1.75V/cell)
Approx. Weight	300g(0.66lbs.)
Terminals	T1 (Faston Tab 187)
Internal Resistance	≤55m Ω (Fully Charged)
Max. Discharge Current	18 A (5 sec.)
Max. Charge Current	0.36 A
Operating Temperature Range	Charge : 0°C~40°C(32°F~104°F) Discharge : -20°C~50°C(-4°F~122°F) Storage. : -20°C~40°C(-4°F~104°F)
Container Material	Standard: ABS(UL 94-HB) BP1.2-6 Optional: Flame Retardant ABS(UL 94-V0) BP1.2-6FR

<ul style="list-style-type: none"> ● IEC 61056-1 ● JIS C 8702-1 ● GB/T 19639.1 	

DIMENSION(mm/inch)	OUTER DIMENSIONS	TERMINAL TYPE
<ul style="list-style-type: none"> ■ Length 97±1.5 (3.82±0.06) ■ Width 25±1.5 (0.98±0.06) ■ Container Height 51±1.5 (2.01±0.06) ■ Total Height 56±2.0 (2.20±0.08) 		<ul style="list-style-type: none"> ● Terminal T1

Constant power discharge characteristics at 25 °C/77 °F Unit: W

F.V. (V/cell) \ Discharge Time	5 Min	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	21.69	15.97	12.80	7.61	4.367	1.749	1.206	0.674	0.355
1.75V	25.11	17.30	13.39	7.90	4.498	1.784	1.224	0.684	0.360
1.70V	26.68	17.92	13.80	8.08	4.579	1.800	1.231	0.687	0.360
1.65V	27.88	18.35	14.12	8.20	4.634	1.813	1.235	0.689	0.360
1.60V	28.80	18.72	14.40	8.28	4.680	1.823	1.239	0.689	0.360

Constant current discharge characteristics at 25 °C/77 °F Unit: A

F.V. (V/cell) \ Discharge Time	5 Min	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	3.91	2.81	2.23	1.291	0.734	0.291	0.201	0.112	0.059
1.75V	4.61	3.05	2.33	1.340	0.756	0.297	0.204	0.114	0.060
1.70V	4.89	3.16	2.40	1.370	0.770	0.300	0.205	0.115	0.060
1.65V	5.11	3.23	2.46	1.389	0.779	0.302	0.206	0.115	0.060
1.60V	5.28	3.30	2.50	1.403	0.787	0.304	0.206	0.115	0.060

All data and artworks shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.