

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Littelfuse](#)
[178.6152.0002](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

Blade Fuseholders - FKH Stackable Fuseholder for ATO® Style Blade Fuse Rated 80V

RoHS





Specifications

Housing + Adapter: Out of thermoplastic (UL 94-V0, heat-resistant)
Connections: Leaf spring connector systems, soldering terminals, copper alloy, tinned
Color: Black

Dimensions in mm / Maße in mm

Fuseholder for ATO / FKS size fuses-links. Attachable in X - direction. Rated voltage 80V; crimp terminals.

Sicherungshalter für Sicherungen in ATO / FKS-Größe. Montage in X-Richtung. Nennspannung 80V, Crimp-Kontakte.



| Part Number Artikel-Nr. | Description Beschreibung | Contact Temperature Kontakttemperatur |
|----------------------------|---|--|
| 178.6152.000_ | Complete | max. 130°C |
| 178.6150.000_ | Housing | - |
| 178.6116.250_ | Complete with 1.5 - 2.5 mm ² | max. 130°C |
| 178.6152.250_ | With 200 mm wiring loop | - |
| 178.6191.000_ | Adapter right | - |
| 178.6192.000_ | Adapter left | - |

Last figure of part number = packaging code, see Section "Packaging Index," pg. 157.

Corresponding fuse links see Section "Blade Fuses."

This FKH-Fuseholder can be mounted in row in any number. The fixing adapters are not included in the fuseholder. Please order the adapter separately.