

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Pomona Electronics 6358

For any questions, you can email us directly: <a href="mailto:sales@integrated-circuit.com">sales@integrated-circuit.com</a>


### **Distributor of Pomona Electronics: Excellent Integrated System Limited**

Datasheet of 6358 - PLUG STR DMM TO RETRACTABLE PLUG

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

## Pomona®

# Model 6358 Test Lead, Straight DMM Plug To Retractable Plug



#### **FEATURES:**

- Fits Fluke, Amprobe, H-P, Tekronix, Wavetek and Amprobe DMM's with sheathed style safety jacks.
- Flexible test leads feature high strand count silcone wire for extreme flexibility and high temperature. resistance. Banana plugs are double crimped to the wire and the plugs are molded directly to the wire for added pull strength.
- The retractable sheath is ideal for connecting to older test equipment without double insulated jacks.

#### **MATERIALS:**

Test Leads (Male to Male) - Multi-Stranded Wire: 18 AWG Silicone, Color: One Black, One Red

Banana Plug: Insulation: Polypropylene, Color: One Black, One Red

Retractable Sheath Banana Plug:

Plug Body: Brass, Nickel Plated

Banana Spring: Beryllium Copper, Nickel Plated

Compression Spring: Stainless Steel

Tip: Polypropylene, Color Matches Color of Wire

Insulation: Polypropylene Molded to the Plug and Wire. Color Matches Color or Wire.

Wire: 18 AWG, Stranding 65 x 36 t.c., Silicone Insulated, .144 (3,66mm) O.D.

#### **RATINGS:**

Operating Temperature: +55° C (+131° F) Max.

Conforms to IEC 1010, Cat. III, P2

Operating Voltage: 1000V Current: 10 Amperes

**ORDERING INFORMATION:** Model 6358

**USA:** Sales: 800-490-2361

Technical Support: technicalsupport@pomonatest.com

Fax: 425-446-5844

**Europe:** 31-(0) 40 2675 150 **International**: 425-446-5500

All dimensions are in inches. Tolerances (except noted):  $.xx = \pm .02$ " (.51 mm),  $.xxx = \pm .005$ " (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

Copyright © 2007 11/09/2007