

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:


[Sullins Connector Solutions](#)
[PTC06DBBN](#)

For any questions, you can email us directly:



sales@integrated-circuit.com

SULLINS PART NUMBER PTC06DBBN


SULLINS ELECTRONICS CORP
 SAN MARCOS, CA 760-744-0125 FAX 760-744-6081



A = 0.600+-0.020 [15.24+-0.51]
B = 0.500+-0.008 [12.70+-0.20]
C = 0.100+-0.003 [2.54+-0.08]
D = 0.240+-0.005 [6.10+-0.13]
E = 0.050+-0.005 [1.27+-0.13]
F = 0.100+-0.005 [2.54+-0.13]
G = 0.230+-0.015 [5.84+-0.38]
H = 0.100+-0.005 [2.54+-0.13]
I = 0.060+-0.005 [1.52+-0.13]
J = 0.100+-0.005 [2.54+-0.13]
K = 0.200+-0.015 [5.08+-0.38]



.025[0.64] SQUARE POSTS FIT .040[1.02] MINIMUM DIAMETER HOLE



Right angle bent tails not shown in bottom view

- 1.0 SPECIFICATIONS FOR A DUAL 6/12 POSITION HEADER
- 2.0 INSULATOR MATERIAL: BLACK THERMOPLASTIC POLYESTER
- 3.0 CONTACT MATERIAL: CA510, PHOSPHOR BRONZE GRADE A
- 4.0 PLATING: .000100" TIN OVERALL, .000050" NICKEL UNDERPLATE
- 5.0 TEMPERATURE: TO 125 DEGREES C CONTINUOUS
- 6.0 UL FLAMMABILITY RATING: 94V-0
- 7.0 VOLTAGE RATING: 600 VDC MINIMUM AT SEA LEVEL
- 8.0 CURRENT RATING: 3 AMPERES
- 9.0 INSULATION RESISTANCE: 5,000 MEGA OHMS
- 10.0 SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
- 11.0 NOT DRAWN TO SCALE

SULLINS PART NUMBER: PTC06DBBN

DATE: 1-29-03

[Print PDF](#)