Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

ASSMANN WSW Components
AK-CHMF-015

For any questions, you can email us directly:
sales@integrated-circuit.com



Material:

1.Cable: Non-UL [26(10/0.12)*1C Tinned Copper Insulation: PVC+
Spiral Shield(28/0.12) Tinned Copper]*2 Flat, Jacket; PVC
OD:⌀2.8*5.6±0.15mm Color:Black(NK-KO1)
2.Connectors:P1&P2: RCA Plug Nickel Plated
P3&P4: RCA Jack Nickel Plated
3.Hood: P1&P3: Molded Type, PVC 45P, Color: White(NK-WO1)
P3&P4: Molded Type, PVC 45P, Color:Red(NK-RO1)
4.Test Request: <1>. 100% Open Short & MIS Wire Test
<2> Insulation Resistance 1M min
5.Packing: Seep-0039 Rev.B Packing Drawing
EAN Code:4016032051329
(Binding size must be smaller than blister)
6.Blister Size: DB VP2

PIN Out

P1		P3
Cond	White	Cond
Shell	Spiral	Shell

PIN Out

P2		P4
Cond	Red	Cond
Shell	Spiral	Shell

RoHS Compliant

ITEM NO	AK-CHMF-015-R (1.5M) AK-CHMF-R (2.0M) AK-CHMF-025-R (2.5M) AK-CHMF-050-R (5.0M)
TITLE	Cinch Extension Cable, Molded Hoods 2 x Cinch Male to 2 x Cinch Female

ASSMANN Electronics, Inc.
1840 W. Drake Drive, Suite 101 - Tempe, AZ 85283
Toll Free: 1-877-277-6266 Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
©Copyright 2008 by Assmann Electronic Components
All International Rights Reserved