

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[TDK Corporation](#)

[HFC-2L-3](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

High Voltage Feed Through Ceramic Capacitors

For magnetron

HFC(Edc: 10kV) series


Issue date: June 2006

High Voltage Feed Through Ceramic Capacitors For Magnetron HFC Series


Conformity to RoHS Directive

FEATURES

- Effectively suppresses noise radiation over a wide frequency range.
- Excellent high-frequency characteristics.
- Compact and lightweight.
- Flame retardant (equivalent to UL94V-1).



SHAPES AND DIMENSIONS




• Faston® is a registered trademark of Tyco Electronics AMP Corp. Incorporated.

CHARACTERISTICS

Rated voltage E _{dc}	10kV
Withstand voltage Er _{ms}	10kV[50Hz, 1min]
Initial insulation resistance	10000M Ω min.
Rated capacitance and tolerance	500pF \pm 35%[1V, 1kHz]
tan δ	1% max.
Capacitance temperature characteristics	E(+20, -55%)
Operating temperature range	-30 to +120°C

FREQUENCY CHARACTERISTICS



- For more information about the products of other capacitance or data, please contact us.
- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.