

# **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Fairchild Semiconductor 1N4149

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



## FAIRCHILD

SEMICONDUCTOR®

## **1N4149** Small Signal Diode



#### DO-35 Color Band Denotes Cathode

## Absolute Maximum Ratings \* $T_a = 25^{\circ}C$ unless otherwise noted

Symbol	Parameter	Value	Unit	
V <sub>RRM</sub>	Maximum Repetitive Reverse Voltage	100	V	
I <sub>F(AV)</sub>	Average Rectified Forward Current	500	mA	
I <sub>FSM</sub>	Non-repetitive Peak Forward Surge Current Pulse Width = 1.0 second Pulse Width = 1.0 microsecond	1.0 4.0	A A	
T <sub>STG</sub>	Storage Temperature Range	-65 to +200	°C	
TJ	Operating Junction Temperature	175	°C	

\* These ratings are limiting values above which the serviceability of the diode may be impaired.

NOTES:

1) These ratings are based on a maximum junction temperature of 200 degrees C.

2) These are steady limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.

## **Thermal Characteristics**

Symbol	Parameter	Value	Unit
P <sub>D</sub>	Power Dissipation	500	mW
$R_{\thetaJA}$	Thermal Resistance, Junction to Ambient	300	°C/W

Electrical Characteristics T<sub>C</sub> = 25°C unless otherwise noted

Symbol	Parameter	Conditions	Min.	Max	Units
V <sub>R</sub>	Breakdown Voltage	I <sub>R</sub> = 5μA I <sub>R</sub> = 100μA	75 100		V V
V <sub>F</sub>	Forward Voltage	I <sub>F</sub> = 10mA		1.0	V
I <sub>R</sub>	Reverse Leakage	V <sub>R</sub> = 20V V <sub>R</sub> = 20V, T <sub>A</sub> = 150°C		25 50	nA μA
CT	Total Capacitance	V <sub>R</sub> = 0, f = 1.0MHz		2	pF
t <sub>rr</sub>	Reverse Recovery Time	$I_F = 10mA, V_R = 6.0V$ $R_L = 100\Omega, I_{rr} = 1mA$		4	ns

December 2004



TRADEMARKS				
Ũ	egistered and unregistered an exhaustive list of all such		iconductor owns or is author	rized to use and is
ACEx <sup>™</sup> ActiveArray <sup>™</sup> Bottomless <sup>™</sup> CoolFET <sup>™</sup> <i>CROSSVOLT</i> <sup>™</sup> DOME <sup>™</sup> EcoSPARK <sup>™</sup> E <sup>2</sup> CMOS <sup>™</sup> EnSigna <sup>™</sup> FACT <sup>™</sup> FACT Quiet Seri	FAST <sup>®</sup> FASTr <sup>™</sup> FPS <sup>™</sup> FRFET <sup>™</sup> GlobalOptoisolator <sup>™</sup> GTO <sup>™</sup> HiSeC <sup>™</sup> I <sup>2</sup> C <sup>™</sup> <i>i-Lo</i> <sup>™</sup> ImpliedDisconnect <sup>™</sup> es <sup>™</sup> d. Around the world. <sup>™</sup>	ISOPLANAR <sup>™</sup> LittleFET <sup>™</sup> MICROCOUPLER <sup>™</sup> MicroFET <sup>™</sup> MicroPak <sup>™</sup> MICROWIRE <sup>™</sup> MSX <sup>™</sup> MSXPro <sup>™</sup> OCX <sup>™</sup> OCX <sup>™</sup> OCXPro <sup>™</sup> OPTOLOGIC <sup>®</sup> OPTOPLANAR <sup>™</sup> PACMAN <sup>™</sup>	PowerTrench <sup>®</sup> QFET <sup>®</sup> QS <sup>TM</sup> QT Optoelectronics <sup>TM</sup> Quiet Series <sup>TM</sup> RapidConfigure <sup>TM</sup> RapidConnect <sup>TM</sup> $\mu$ SerDes <sup>TM</sup> SILENT SWITCHER <sup>®</sup> SMART START <sup>TM</sup>	Stealth <sup>™</sup> SuperFET <sup>™</sup> SuperSOT <sup>™</sup> -3 SuperSOT <sup>™</sup> -6 SuperSOT <sup>™</sup> -8 SyncFET <sup>™</sup> TinyLogic <sup>®</sup> TINYOPTO <sup>™</sup> TruTranslation <sup>™</sup> UHC <sup>™</sup> UltraFET <sup>®</sup> UniFET <sup>™</sup> VCX <sup>™</sup>
Programmable Active Droop™ POP™ SPM™   DISCLAIMER				

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

### LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user. 2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

### PRODUCT STATUS DEFINITIONS

#### Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.
Rev. I1		