

Excellent Integrated System Limited


Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[FCI](#)
[65039-001LF](#)


For any questions, you can email us directly:

sales@integrated-circuit.com

PRODUCT NUMBER
65039-YXX(E)LFDESIGN CODE
0 = STANDARD
2 = OPTIONAL RIB
SEE SHEET 2INDICATES THE PRODUCT IS RoHS
COMPLIANT, SEE NOTE 6PIN STYLE
SEE SHEET 265039-YXXLF OR 65039-YXXELF ARE
EXACTLY THE SAME PRODUCTS.
EXTENSION "E" JUST FOR OLD EUROPEAN
DESIGN AND MANUFACTURING SITE

NOTES:

1. MOLDING MATERIAL : MODIFIED POLYPHELYNE
COLOR BLACK, UL 94 V0
2. LATCH MUST WITHSTAND 18N MIN PULL OUT FORCE
3. STANDARD PACKAGING IN POLYBAGS
4. TERMINALS MUST BE CRIMPED PROPERLY FOR
SATISFACTORY LATCHING :
 - FOR CRIMPING INSTRUCTIONS, SEE TA-75 AND TA-295
 - FOR TERMINAL APPLICATION SEE TA-531.PRODUCT SPECIFICATION: BUS-12-067.
5. THIS HOUSING IS INTENDED FOR USE WITH
MINI PV TERMINAL WITH 22-36 GAUGE WIRE
6. RoHS COMPLIANT PRODUCT SPECIFICATIONS :
 - MEETS PACKAGING SPECS AS PER GS-14-920
 - PRODUCT MEETS EUROPEAN UNION DIRECTIVES
AND OTHER COUNTRY REGULATIONS AS
DESCRIBED IN GS-22-008.
 - THE PRODUCT IS NOT INTENDED TO BE EXPOSED
TO A MANUFACTURING SOLDER PROCESS.




mat'l. code				surface	tolerance	projection	product family	
SEE NOTES				ISO 1302	ISO 406 ISO 1101		BERCONN	
lfr	ecm no	dr	date	tolerances unless otherwise specified			title	
BE	V07-0483	HTB	07.07.24	angles	.x ±0.3	mm	MINI LATCH SR	
BF	F12-0064	LMU	12.06.08		.xx ±0.13			
BG	B-14321	LMU	13.03.21		.xxx ±0.05	scale 5:1	POLARIZED HSG 2.54mm	
BH	B-18693	LMU	14.08.29	dr	L.MULIN	12.06.08	dwg no	sheet 1 of 2 size
BJ	B-20324	AMA	15.02.27	engr	L.MULIN	12.06.08	65039	A3
				chr				
				appd	JCO	12.06.08	type	CUSTOMER Drawing
sheet	revision	BJ	BH					
index	sheet	1	2					

PDS: Rev:BJ

STATUS:Released

Printed: Mar 03, 2015

PIN STYLE	No. OF POS.	DIM J	DIM K
36	1x01	N/A	2.39
35	1x02	2.54	4.93
34	1x03	5.08	7.47
33	1x04	7.62	10.01
32	1x05	10.16	12.55
31	1x06	12.70	15.09
30	1x07	15.24	17.63
29	1x08	17.78	20.17
28	1x09	20.32	22.71
27	1x10	22.86	25.25
26	1x11	25.40	27.79
25	1x12	27.94	30.33
24	1x13	30.48	32.87
23	1x14	33.02	35.41
22	1x15	35.56	37.95
21	1x16	38.10	40.49
20	1x17	40.64	43.03
19	1x18	43.18	45.57
18	1x19	45.72	48.11
17	1x20	48.26	50.65
16	1x21	50.80	53.19
15	1x22	53.34	55.73
14	1x23	55.88	58.27
13	1x24	58.42	60.81
12	1x25	60.96	63.35
11	1x26	63.50	65.89
10	1x27	66.04	68.43
09	1x28	68.58	70.97
08	1x29	71.12	73.51
07	1x30	73.66	76.05
06	1x31	76.20	78.59
05	1x32	78.74	81.13
04	1x33	81.28	83.67
03	1x34	83.82	86.21
02	1x35	86.36	88.75
01	1x36	88.90	91.29



mat'l. code				surface ISO 1302	tolerance ISO 406 ISO 1101	projection 	product family BERCONN	
ltr	ecp no	dr	date	tolerances unless otherwise specified		mm	title	
BE	V07-0483	HTB	07.07.24	angles	linear	.x ±0.3	MINI LATCH SR	
BF	F12-0064	LMU	12.06.08			.xx ±0.13	POLARIZED HSG 2.54mm	
BG	B-18693	LMU	14.08.29			.xxx ±0.05	scale 5:1	
BH	B-20324	AMA	15.02.27	dr	L.MULIN	12.06.08	FCI	
				enrg	L.MULIN	12.06.08	dwg no	
				chr			65039	
				appd	JCO	12.06.08	sheet 2 of	
sheet index	revision sheet						type	
							CUSTOMER Drawing	