

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:


[Visual Communications Company, LLC](#)  
[5210F1](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

## 5210F Series Panel Mounted LED Indicator Light

### Description and Features



#### Features

This is an insulated lead version of the 5200F Series Sub-miniature Super Brite LED assembly that offer superior performance in a package that is economical to buy and install. This series gives protection against static discharge.

Mounting: Will snap-fit into Ø.187/.192 hole in panels .020/.097 thick

Wire leads: No. 26 AWG, 4.4/4.8 long, stripped .180/.320

Anode(+): Red lead

Lens: Polycarbonate

Housing: Polycarbonate

### Electro-optical Characteristics

Part Number	Color	Typ. Intensity (mcd)	Rated Current (mA)	Continuous Forward Current Max. (mA)	Forward Voltage Typ. (V)	Forward Voltage Max. (V)	Peak Forward Current @ 1ms-300pps (A)	Reverse Break-down Voltage Min. (V)
5210F1	Red	6.0	10	30	2.0	3.0	1.0	5
5210F5	Green	12.0	20	30	2.2	3.0	.09	5
5210F7	Yellow	20.0	20	30	2.1	3.0	3.0	5
5210F6-5V	Blue	(Uses #680 lamp, incandescent 200,000 hours, 5V, .06A)						