

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Panasonic Electronic Components](#)

[EEC-EP0E333A](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

Panasonic

Electric Double Layer Capacitors (Gold Capacitor)/ EP

Surface Mount Type

Series: **EP**



■ Features

- Miniaturized : Dia3.8 × height 1.5 mm max.
- Reflow soldering method available (260 °C)
- RoHS directive compliant

■ Recommended Applications


- Mobile phones, PDAs
- RTC backup

■ Specifications

Category	Temp. Range	-10 °C to +60 °C	
Maximum Operating Voltage		2.6 V DC	3.3 V DC
Nominal capacitance	0.033 F		
Characteristics at Low Temperature	Capacitance change	±30 % of initial measured value at 20 °C (at -10°C)	
	Internal resistance	≤10 times of initial measured value at 20 °C (at -10°C)	
Endurance		After 500 hours application of 2.6 V at +60 °C	After 250 hours application of 3.3 V at +60 °C
	Capacitance change	±30 % of initial measured value at 20 °C	Capacitance change
	Internal resistance	2 kΩ or less	Internal resistance
Shelf Life	After 500 hours strage at +60 °C without load (voltage)		
	Capacitance change	±30 % of initial measured value at 20 °C	
	Internal resistance	1 kΩ or less	

■ Dimensions in mm(not to scale)

(Unit : mm)



■ Standard Products

Maximum Operating Voltage (V.DC)	Capacitance (F)	Capacitance tolerance	Internal resistance (Initial specified value) (Ω) at 1 kHz	Maximum discharging current (μA)	Part number	Mass (g)	Min. Packaging Q'ty (pcs)
2.6	0.033	- 20% to +80%	≤350	5	EECEP0E333()	0.06	4000
3.3					EECEP0F333()		

() Please use A or Y, to indicate the terminal style.

The re-flow condition / taping dimensions are explained on EE210, EE211 of our catalog.

Note : 1. Do not use reflow soldering when cell voltage is above 0.3 V.

2. When the capacitor is being used in a high temperature and high humidity environment for a long period, and will not affect any electrical characteristics of the capacitor.

3: EP series is a small capacitor that developed for the RTC backup of cellular phone. Therefore, there is a possibility that it will not be able to back up in short term depend on using condition. Please contact us before you use it