

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:



[NorComp](#)
[6845W1103L461](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

DESCRIPTION: POWER / SIGNAL - RIGHT ANGLE - MALE

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com



SPECIFICATIONS:

ELECTRICAL

INSULATOR RESISTANCE:	5,000 MegOHMS Min.
DIELECTRIC WITHSTANDING:	1,000VAC r.m.s.
OPERATING TEMPERATURE:	-55° C ~ +125° C
CONTACT RESISTANCE:	30 Milliohms Max.
POWER PINS:	40 AMPS
SIGNAL PINS:	5 AMPS

MECHANICAL:

CONTACT INSERTION FORCE:	4.5 Kg Max.
CONTACT SEPARATOR FORCE:	0.3Kg Min.

MATERIALS:

CONTACTS:	BRASS
INSULATOR:	PBT UL94V-0 RATED, 230°C PROCESS TEMP.
SHELL:	STEEL
BOARD LOCK:	BRASS, NICKEL PLATED
CINCHNUT:	BRASS, NICKEL PLATED
BRACKET:	STEEL, NICKEL PLATED

FINISH:

SHELL:	NICKEL
--------	--------

6845W1103L461

46 = 4-40 INSERTS /
BOARD LOCKS

RoHS COMPLIANT

	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWN:		DATE:		
		C. SMITH		10-06-06		
NorComp		CHECKED:		DATE:		
		SCALE:		SHEET OF		REV
		1.5 = 1		1 2		2
		DWG NO.		6845W1103L461		

