

Excellent Integrated System Limited


Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Desco](#)
[47508](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



CAUTION
This Bag Contains
MOISTURE-SENSITIVE DEVICES

LEVEL

If blank, see adjacent bar code label

1. Calculated shelf life in sealed bag: 12 months at <40°C and <90% relative humidity (RH).
2. Peak package body temperature: _____ °C
If blank, see adjacent bar code label
3. After bag is opened, devices that will be subjected to reflow solder or other high temperature process must
a) Mounted within _____ hrs of factory conditions
If blank, see adjacent bar code label
≤30°C/60% RH, OR
b) Stored at ≤10% RH.
4. Devices require baking, before mounting, if :
a) Humidity Indicator Card is >10% when read at 23 ±5°C.
b) If 3a or 3b are not met.
5. If baking is required, devices may be baked for 48 hrs. at 125±5°C
Note: If device containers cannot be subjected to high temperature or shorter bake times are desired.
reference IPC/JEDEC J-STD-033 for bake

Bag Seal Date: _____
If blank, see adjacent bar code label

Note: Level and body temperature defined by IPC/JEDEC J-STD-020

STATSHIELD® SERIES
www.descoindustries.com

**Moisture Warning
Symbol and
message clearly
shown on label.**

Item	Description	Qty/Roll
47508	3" x 3", Permanent	250

COLOR: White with blue printing

SYMBOL: JEDEC JEP 113

PACKAGED: 250 per roll, 3" diameter core

DESCRIPTION: The product is designed for dry packing applications; the label provides the moisture warning symbol and displays a warning message needed to complete your dry package system. The label is tamper evident, allowing you to easily monitor whether or not the MBB has been opened. The permanent adhesive label is designed for use on all Protektive Pak Statshield® Moisture Barrier Bags that are used in the dry packing of SMD tape and reel, quad flat pack/JEDEC trays, and component shipping tubes

PRODUCT SPECIFICATIONS:

Adhesive: B-82, strong and permanent
 Liner: 40# white Kraft
 Facestock: 60# SemiGloss Litho
 Service Temperature: -10 to +180°F
 Minimum Labelling Temperature: +15°F

INK & VARNISH SPECIFICATIONS:

Water Resistance: Excellent
 Grease Resistance: Excellent
 Alcohol Resistance: Excellent
 UV Resistance: Excellent

FEATURES

- ☐ 250 labels per roll
- ☐ White label with blue printing
- ☐ Coated with an ultra violet varnish for added durability
- ☐ Strong, permanent adhesive
- ☐ Labels are mounted on a 3" core for use in tape dispensers
- ☐ Tamper evident



Made in America

LABEL, MOISTURE SENSITIVE, CAUTION, JEDEC JEP 113

PROTEKTIVE PAK

PROTEKTIVE PAK
 13520 MONTE VISTA AVENUE, CHINO, CA 91710
 PHONE (909) 627-2578, FAX (909) 363-7331
www.protektivepak.com

DRAWING NUMBER
47508

DATE:
7/05