Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

3M 4270-48Y

For any questions, you can email us directly: sales@integrated-circuit.com



Distributor of 3M: Excellent Integrated System Limited

Datasheet of 4270-48Y - COVER CIRCULAR 2.88" ID 250PCS

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

3M™ Connector Covers

Circular and "D" Type Conductive Covers

3M Connector Covers are made of an intrinsically conductive composite material with uniformly distributed fibers. This makes the covers free of carbon black particulate and better suited to clean situations. The covers do not leave black marks and are permanently

3M™ Circular Connector Covers 4270 Series

4270 Series were designed to meet the requirements and intentions of MS90376, and MIL PRF 5501/31A or 2A. Military contractors have qualified these materials to their own specifications and are encouraging their use.



3M "D" Type Connector Covers 4272 Series 4272 Series were designed to meet the requirements

and intentions of MIL-PRF-5501. Military contractors have qualified these materials to their own specifications and are encouraging their use.



Specifications

Typical Properties:

Resistivity Contact Corrosivity (Kovar plate) Crayoning Elongation Tensile

Vicat Softening Outgassing ASTM ASTM D991 FTMS 101C Method 3005 3M

ASTM D638 ASTM D638 ASTM MD E595

<105 ohm-cm Pass

Not visible 25% 1500 PSI (1.0 x 107 N/m2) 1525 205°F (96OC)

Chemical Reactions

Dilute Acids Dilute Alkalines Concentrated Acids Concentrated Alkalines Methanol, Ethanol, and Isopropanol Hydrocarbons Ketones Oil and Gasoline

Slight Attack Slight Attack Severe Attack Severe Attack Resistant

Slight Attack Dissolves Severe Attack

P R O D U C T D A Т Α Е Е

4270 and 4272 Series Connector Covers

PRODUCT
CONDUCTIVE CONNECTOR COVERS

ITEM_NUMBER

DATASHEET 4270

3M Electronics Solutions Division SM Electronics Solidations Division 6801 River Place Blvd Austin, TX 78726-9000 US and Canada: 866-722-3736 Fax: 866-722-3735 Intl: 919-718-0000: Fax: 919-774-8174 email: 3Mstaticinfo@mmm.com; www.3Mstatic.com 3M is a trademark of 3M Company. All other trademarks herein are the property of their respective owners.

See page 2 for sizes





Distributor of 3M: Excellent Integrated System Limited

Datasheet of 4270-48Y - COVER CIRCULAR 2.88" ID 250PCS

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

3M™ Circular Connector Covers 4270 Series

Packaged 100/bag: 10 bags/box


| Product | Α | В | С | D | |
|-------------|-------|------|-------|-------|--|
| Description | | | | | |
| 4270-4R | .670 | .500 | .250 | .336 | |
| 4270-5R | .670 | .500 | .313 | .399 | |
| 4270-6R | .670 | .500 | .375 | .461 | |
| 4270-8Y | .670 | .625 | .413 | .483 | |
| 4270-8R | .740 | .500 | .480 | .540 | |
| 4270-9R | .750 | .500 | .500 | .586 | |
| 4270-10Y | .750 | .625 | .530 | .595 | |
| 4270-10R | .840 | .500 | .605 | .665 | |
| 4270-12Y | .860 | .625 | .655 | .715 | |
| 4270-12R | .970 | .500 | .720 | .775 | |
| 4270-14Y | 1.031 | .625 | .785 | .845 | |
| 4270-14R | 1.125 | .500 | .850 | .905 | |
| 4270-16Y | 1.125 | .625 | .893 | .963 | |
| 4270-16R | 1.220 | .500 | .973 | 1.035 | |
| 4270-18Y | 1.250 | .625 | 1.028 | 1.088 | |
| 4270-18R | 1.330 | .562 | 1.093 | 1.155 | |
| 4270-19R | 1.400 | .562 | 1.125 | 1.213 | |

Packaged 50/bag: 10 bags/box

| Product | Α | В | С | D | |
|-------------|-------|------|-------|-------|--|
| Description | | | | | |
| 4270-20Y | 1.406 | .625 | 1.150 | 1.215 | |
| 4270-20R | 1.465 | .562 | 1.231 | 1.301 | |
| 4270-22Y | 1.500 | .625 | 1.270 | 1.340 | |
| 4270-22R | 1.590 | .562 | 1.340 | 1.410 | |
| 4270-24Y | 1.640 | .625 | 1.390 | 1.460 | |
| 4270-24R | 1.700 | .562 | 1.463 | 1.533 | |
| 4270-25Y | 1.810 | .625 | 1.540 | 1.580 | |
| 4270-28Y | 1.875 | .625 | 1.645 | 1.718 | |
| 4270-28R | 1.950 | .562 | 1.715 | 1.790 | |

Packaged 25/bag: 10 bags/box

| Product | Α | В | С | D | |
|-------------|-------|------|-------|-------|--|
| Description | | | | | |
| 4270-32Y | 2.125 | .625 | 1.890 | 1.970 | |
| 4270-32R | 2.220 | .562 | 1.965 | 2.040 | |
| 4270-36Y | 2.340 | .625 | 2.140 | 2.210 | |
| 4270-36R | 2.435 | .600 | 2.215 | 2.290 | |
| 4270-40Y | 2.600 | .625 | 2.380 | 2.450 | |
| 4270-40R | 2.660 | .600 | 2.440 | 2.530 | |
| 4270-44Y | 2.875 | .625 | 2.630 | 2.700 | |
| 4270-44R | 2.960 | .600 | 2.720 | 2.812 | |
| 4270-48Y | 3.125 | .625 | 2.880 | 2.950 | |
| 4270-48R | 3.225 | .600 | 2.960 | 3.050 | |







3M "D" Type Connector Covers 4272 Series

Packaged 100/bag: 10 bags/box

| Product | Α | В | С | D | Е | F | G | Н |
|-------------|-------|-------|-------|------|------|------|------|------|
| Description | | | | | | | | |
| 4272-50P | 2.112 | 2.179 | 2.279 | .636 | .536 | .469 | .280 | .240 |
| 4272-50S | 2.049 | 2.116 | 2.216 | .574 | .474 | .407 | .280 | .240 |
| 4272-37P | 2.216 | 2.283 | 2.383 | .530 | .430 | .363 | .280 | .240 |
| 4272-37S | 2.143 | 2.210 | 2.310 | .462 | .362 | .295 | .280 | .240 |
| 4272-25P | 1.586 | 1.635 | 1.735 | .530 | .430 | .363 | .280 | .240 |
| 4272-25S | 1.495 | 1.562 | 1.662 | .462 | .362 | .295 | .280 | .240 |
| 4272-15P | 1.040 | 1.107 | 1.177 | .512 | .436 | .369 | .280 | .240 |
| 4272-15S | .955 | 1.022 | 1.122 | .462 | .362 | .295 | .280 | .240 |
| 4272-9P | .708 | .775 | .849 | .512 | .434 | .367 | .280 | .240 |
| 4272-9S | .627 | .694 | .794 | .462 | .362 | .295 | .280 | .240 |





All statements, technical information, and recommendations related to All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.
This product will be free from defects in material and manufacture as of the date of purchases. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.

4270 and 4272 Series Connector Covers

CONDUCTIVE CONNECTOR COVERS

ITEM_NUMBER SEE TABLE

С

DATASHEET 4270

3M Electronics Solutions Division 6801 River Place Blvd Austin, TX 78726-9000 US and Canada: 866-722-3736 Fax: 866-722-3735 Intl: 919-718-0000; Fax: 919-774-8174 email: 3Mstaticinfo@mmm.com; www.3Mstatic.com

3M is a trademark of 3M Company All other trademarks herein are the property of their respective owners.

