

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Tripp Lite](#)  
[ISOBAR8 ULTRA](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

## Isobar 8-Outlet Surge Protector, 12-ft. Cord, 3840 Joules

MODEL NUMBER: ISOBAR8ULTRA



### Highlights

- 8 outlets/12-ft cord
- 3840 joule rating—more joules mean more protection!
- All-metal housing with diagnostic LEDs
- Isolated filter banks remove damaging line noise
- \$50,000 Ultimate Lifetime Insurance for connected equipment (U.S., Canada, and Puerto Rico only)

### Package Includes

- ISOBAR8ULTRA Surge Protector
- Set of 4 outlet safety covers
- Instruction manual with warranty information

### Description

For more than 20 years, America's leading companies have trusted Tripp Lite's Isobar Premium surge and noise protectors to protect sensitive computer, networking and telecom equipment. With more than 18 million satisfied customers, the Isobar remains the world's #1 selling premium surge protector. Loaded with a generous combination of high quality components, near indestructible all-metal case and unique noise filtration system, the Isobar offers the highest level of protection attainable in a multi-outlet strip. Robust surge suppression circuits with sine-wave tracking offer extreme levels of protection against the heaviest surge conditions exceeding IEEE 587 category A & B specifications and reducing 6,000V test surges to harmless levels under 35 volts. Isobar's unique protection system combines large toroidal chokes, ferrite rod-core inductors, HF/VHF capacitors and multiple layers of metal oxide varistors into exclusive isolated filter banks that remove EMI/RFI interference, even noise generated by other pieces of connected equipment. ISOBAR8ULTRA offers 8 outlets arranged in four filter banks to prevent system crashes, reboots and performance problems common as noisy system peripherals are powered off and on. Surge suppression rated at 3840 joules/97,000 amps offers network-grade protection. Widely spaced NEMA 5-15 outlets accommodate up to 4 large transformer plugs without blocking outlets. Diagnostic LEDs confirm power availability, line fault and protection status. Includes 12 foot AC line cord with space-saving angled input plug, keyhole mounting tabs and a set of 4 child safety covers.

PLUG/OUTLETS: Input: NEMA 5-15P/Output: 8 NEMA5-15R/12-ft. AC line cord

ELECTRICAL: 120V AC, 50/60Hz (Requires NEMA 5-15R wall receptacle)

SUPPRESSION: AC: 140V RMS Clamping/3840 joules/97,000 amps

FORMAT: Corded all-metal strip with transformer spaced outlets

### Features

- Tripp Lite's ISOBAR is the world's #1 selling premium protector series with more than 18 million satisfied customers and a safety-tested history of 20+ years
- Robust surge suppression with sine-wave tracking protects against the heaviest of surge conditions, exceeding IEEE category A&B specifications and reducing 6,000V test surges to harmless levels less than 35 volts
- Multi-component suppression circuits combine toroidal chokes, ferrite rod-core inductors, HF/VHF capacitors and multiple layers of metal oxide varistors into exclusive isolated filter banks that remove EMI/RFI interference, even noise from other pieces of connected equipment
- 8 outlets arranged in four filter banks prevent system crashes, reboots and performance problems common as noisy peripherals are powered off and on
- Network grade surge suppression rated at 3840 joules/97,000 amps



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

- Widely spaced outlets accommodate up to 4 large transformer plugs without blocking outlets
- 3 LED indicators confirm surge protector operation and site wiring status, plus warning of protector or electrical fault conditions
- Lighted power switch with integrated 12 amp circuit breaker offers power control and overload protection
- 12 foot AC line cord with space-saving angled input plug
- Keyhole mounting tabs allow permanent installation
- Set of 4 outlet covers safely seal off unused outlets
- 120V AC, 50/60Hz electrical compatibility
- \$50,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)
- Automatic shutoff cuts power to outlets when the protection circuit has been compromised

## Specifications

| OUTPUT                             |  |
|------------------------------------|--|
| Frequency Compatibility            | 50 / 60 Hz   |
| Output Receptacles                 | (8) 5-15R  |
| Output (Watts)                     | 1440   |
| Circuit Breaker (amps)             | 12   |
| Transformer Accommodation          | Supports up to 4 large transformer plug accessories without covering remaining outlets |
| Right-Angle Outlets                | No   |
| INPUT                              |  |
| Nominal Input Voltage(s) Supported | 120V AC  |
| Recommended Electrical Service     | 120V (110-125V)  |
| Input Connection Type              | NEMA 5-15P input plug  |
| Input Plug Features                | Space-saving right angle input plug  |
| Input Cord Length (ft.)            | 12   |
| Input Cord Length (m)              | 3.66   |
| Voltage Compatibility (VAC)        | 120  |
| Maximum Surge Amps                 | 150000   |
| Right-Angle Plug                   | Yes  |
| USER INTERFACE, ALERTS & CONTROLS  |  |
| Switches                           | Combination AC circuit breaker and two position red illuminated on/off power switch    |
| Diagnostic LED Details             | PROTECTION PRESENT (green), LINE FAULT (red) and LINE OK (green)                       |
| SURGE / NOISE SUPPRESSION          |  |
| AC Suppression Joule Rating        | 3840   |
| AC Suppression Response Time       | NM = 0 ns. CM = <1 ns  |



**Tripp Lite**  
 1111 W. 35th Street  
 Chicago, IL 60609 USA  
 Telephone: 773.869.1234  
 www.triplite.com

|  |  |
|--|--|
| Protection Modes                                     | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression   |
| Clamping Voltage (RMS)                               | 140  |
| AC Suppression Surge Current Rating                  | 97,000 amps (36,000 NM / 61,000 CM)  |
| AC Suppression Components Used                       | Metal oxide varistors, toroidal balanced chokes, ferrite rod-core inductors and VHF capacitors.  |
| Safe Thermal Fusing                                  | Prevents unsafe conditions during extreme extended over-voltages and catastrophic occurrences  |
| UL1449 Let Through Rating                            | 330V   |
| IEEE587 Cat. A Ringwave Let-Through                  | Less than 35 volts   |
| EMI / RFI Filtering                                  | 40-80 dB   |
| Isolated Filter Banks                                | Unique isolated filter bank design offers additional filtering between each duplex pair of outlets on the strip to prevent electrical noise interference between connected loads. Includes 4 filter banks. |
| Immunity   | Conforms to IEE 587 / ANSI C62.41  |
| <b>DATALINE SURGE SUPPRESSION</b>                    |  |
| Telephone/DSL Protection                             | No   |
| Cable (Coax) Protection                              | No   |
| Network (Ethernet) Protection                        | No   |
| <b>PHYSICAL</b>                                      |  |
| Unit Dimensions (hwd / in.)                          | 2.19 x 3.5 x 8.87  |
| Unit Dimensions (hwd / cm)                           | 5.56 x 8.89 x 22.23  |
| Unit Weight (lbs.)                                   | 3.3  |
| Unit Weight (kg)                                     | 1.50   |
| Material of Construction                             | Metal  |
| Integrated Keyhole Mounting Tabs                     | Metal end caps are fitted with keyhole mounting tabs for wallmount installation  |
| Housing Color  | Light Gray   |
| Receptacle Color                                     | Black  |
| Color (AC Line Cord)                                 | Light Gray   |
| Outlets Measurement (Center to Center)               | Distance between horizontal outlets = 39.45mm; Distance between vertical outlets = 39.30mm   |
| Keyhole Slot Mounting Measurement (Center to Center) | Distance between horizontal tabs = 210.79mm; Distance between vertical tabs = 58.17mm  |
| <b>CERTIFICATIONS</b>                                |  |
| UL1449 3rd Edition (AC Suppression)                  | Tested to UL1449 3rd Edition by ETL  |
| cUL / CSA (Canada)                                   | Approved for Canada by ETL   |
| Approvals  | Exceeds IEEE 587 category A&B specifications   |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

| WARRANTY   |  |
|--|--|
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty                            |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$50,000 <a href="#">Ultimate Lifetime Insurance</a> |

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <http://www.tripplite.com/products/product-certification-agencies>