

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ON Semiconductor](#)
[BD435](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

BD435G, BD437G, BD439G, BD441G

Plastic Medium-Power Silicon NPN Transistors

This series of plastic, medium-power silicon NPN transistors can be used for amplifier and switching applications.

Features

- Complementary Types are BD438 and BD442
- These Devices are Pb-Free and are RoHS Compliant*

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector-Emitter Voltage BD435G BD437G BD439G BD441G	V_{CEO}	32 45 60 80	Vdc
Collector-Base Voltage BD435G BD437G BD439G BD441G	V_{CBO}	32 45 60 80	Vdc
Emitter-Base Voltage	V_{EBO}	5.0	Vdc
Collector Current	I_C	4.0	Adc
Base Current	I_B	1.0	Adc
Total Device Dissipation @ $T_C = 25^\circ\text{C}$ Derate above 25°C	P_D	36 288	W W/ $^\circ\text{C}$
Operating and Storage Junction Temperature Range	T_J, T_{stg}	-55 to +150	$^\circ\text{C}$

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	3.5	$^\circ\text{C/W}$


*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SODERRM/D.



ON Semiconductor®

<http://onsemi.com>

4.0 AMPERES POWER TRANSISTORS NPN SILICON



MARKING DIAGRAM



Y = Year
 WW = Work Week
 BD4xx = Device Code
 xx = 35, 37, 37T, 39, 41
 G = Pb-Free Package

ORDERING INFORMATION

Device	Package	Shipping
BD435G	TO-225 (Pb-Free)	500 Units/Box
BD437G	TO-225 (Pb-Free)	500 Units/Box
BD437TG	TO-225 (Pb-Free)	50 Units/Rail
BD439G	TO-225 (Pb-Free)	500 Units/Box
BD441G	TO-225 (Pb-Free)	500 Units/Box

BD435G, BD437G, BD439G, BD441G

ELECTRICAL CHARACTERISTICS ($T_C = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
Collector-Emitter Breakdown Voltage ($I_C = 100 \text{ mA}$, $I_B = 0$) BD435G BD437G BD439G BD441G	$V_{(\text{BR})\text{CEO}}$	32 45 60 80	— — — —	— — — —	Vdc
Collector-Base Breakdown Voltage ($I_C = 100 \mu\text{A}$, $I_B = 0$) BD435G BD437G BD439G BD441G	$V_{(\text{BR})\text{CBO}}$	32 45 60 80	— — — —	— — — —	Vdc
Emitter-Base Breakdown Voltage ($I_E = 100 \mu\text{A}$, $I_C = 0$)	$V_{(\text{BR})\text{EBO}}$	5.0	—	—	Vdc
Collector Cutoff Current ($V_{CB} = 32 \text{ V}$, $I_E = 0$) BD435G ($V_{CB} = 45 \text{ V}$, $I_E = 0$) BD437G ($V_{CB} = 60 \text{ V}$, $I_E = 0$) BD439G ($V_{CB} = 80 \text{ V}$, $I_E = 0$) BD441G	I_{CBO}	— — — — —	— — — — —	0.1 0.1 0.1 0.1	mA
Emitter Cutoff Current ($V_{EB} = 5.0 \text{ V}$)	I_{EBO}	—	—	1.0	mA
DC Current Gain ($I_C = 10 \text{ mA}$, $V_{CE} = 5.0 \text{ V}$) BD435G BD437G BD439G BD441G	h_{FE}	40 30 20 15	— — — —	— — — —	—
DC Current Gain ($I_C = 500 \text{ mA}$, $V_{CE} = 1.0 \text{ V}$) BD435G BD437G BD439G, BD441G	h_{FE}	85 85 40	— — —	475 375 475	—
DC Current Gain ($I_C = 2.0 \text{ A}$, $V_{CE} = 1.0 \text{ V}$) BD435G BD437G BD439G BD441G	h_{FE}	50 40 25 15	— — — —	— — — —	—
Collector Saturation Voltage ($I_C = 2.0 \text{ A}$, $I_B = 0.2 \text{ V}$) BD435G ($I_C = 3.0 \text{ A}$, $I_B = 0.3 \text{ A}$) BD437G, BD439G, BD441G	$V_{CE(\text{sat})}$	— —	— —	0.5 0.8	Vdc
Base-Emitter On Voltage ($I_C = 2.0 \text{ A}$, $V_{CE} = 1.0 \text{ V}$)	$V_{BE(\text{on})}$	—	—	1.1	Vdc
Current-Gain – Bandwidth Product ($V_{CE} = 1.0 \text{ V}$, $I_C = 250 \text{ mA}$, $f = 1.0 \text{ MHz}$)	f_T	3.0	—	—	MHz

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

BD435G, BD437G, BD439G, BD441G




Figure 1. Collector Saturation Region




Figure 2. Current Gain




Figure 3. "On" Voltage





Figure 4. Active Region Safe Operating Area

BD435G, BD437G, BD439G, BD441G


PACKAGE DIMENSIONS



TO-225
CASE 77-09
ISSUE AC

FRONT VIEW

BACK VIEW



NOTES:
1. DIMENSIONING AND TOLERANCING PER
ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. NUMBER AND SHAPE OF LUGS OPTIONAL.

	MILLIMETERS	
DIM	MIN	MAX
A	2.40	3.00
A1	1.00	1.50
b	0.60	0.90
b2	0.51	0.88
c	0.39	0.63
D	10.60	11.10
E	7.40	7.80
e	2.04	2.54
L	14.50	16.63
L1	1.27	2.54
P	2.90	3.30
Q	3.80	4.20

STYLE 1:
PIN 1. Emitter
2., 4. Collector
3. Base

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada

Europe, Middle East and Africa Technical Support:

Phone: 421 33 790 2910

Japan Customer Focus Center

Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local
Sales Representative