

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Tripp Lite](#)  
[LS604WM](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

## 600W 120V Wall-Mount Power Conditioner with Automatic Voltage Regulation (AVR), AC Surge Protection, 4 Outlets

MODEL NUMBER: **LS604WM**



### Highlights

- Ideal for computers, routers, modems and home theater components
- Corrects under- and overvoltages in 87V–140V range
- Protects against spikes with 720 joules of surge suppression
- Mounts to the wall using included hardware
- Features 4 NEMA 5-15R rear outlets

### Package Includes

- LS604WM 600W 120V Power Conditioner
- Mounting hardware
- Owner's Manual

### Description

The LS604WM 600W 120V Power Conditioner adjusts under- and overvoltages to provide safe, computer-grade AC power that meets ANSI C84.1 specifications. Built-in automatic voltage regulation (AVR) corrects undervoltages as low as 87V and overvoltages as high as 140V back to regulated 120V nominal power. Providing optimum voltage conditions not only extends the life of your equipment, but also keeps your equipment working through brownouts and prolonged overvoltage conditions.

A network-grade 720-joule surge suppression rating conforms to the IEEE-587 standard for surge suppression and prevents spikes from inflicting damage, data loss or corruption and audio/video performance problems on your connected equipment. EMI/RFI noise filtering protects your AC line from disruptive electromagnetic and radio interference.

Just connect the NEMA 5-15P plug with 6-foot cord to an AC power source, and plug up to four devices into the rear NEMA 5-15R outlets. A front-panel LED lets you know your equipment is protected. Secure the LS604WM's all-metal case to a wall or other surface using the built-in mounting tabs and included screws.

### Features

#### Protects Valuable Electronics

- Rated at 120V/600W/5A
- Ideal for computers, routers, modems, printers, home theater components and point-of-sale equipment
- Connect up to 4 electronic devices to the rear NEMA 5-15R outlets
- All-metal case with mounting tabs attaches to wall or other surface using included screws

#### Automatic Voltage Regulation (AVR)

- Monitors incoming AC power and keeps equipment working through brownouts and prolonged overvoltage conditions
- Corrects undervoltages as low as 87V and overvoltages as high as 140V



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

#### AC Line Surge Suppression

- 720 joules of network-grade surge suppression protects against potentially harmful power surges and spikes

#### EMI/RFI Line Noise Filtering

- Removes electromagnetic and radio frequency interference that can disrupt or damage your equipment's performance

#### Built-In Diagnostics

- Front-panel LED indicates your components are protected
- Lighted on/off switch provides one-touch power control over all components

## Specifications

| OUTPUT                              |   |
|-------------------------------------|---|
| Nominal Output Voltage(s) Supported | 120V  |
| Output Receptacles                  | (4) 5-15R   |
| Output (VA)                         | 600   |
| Output (Watts)                      | 600   |
| INPUT                               |   |
| Input Cord Length (ft.)             | 6   |
| Input Cord Length (m)               | 1.83  |
| USER INTERFACE, ALERTS & CONTROLS   |   |
| Front Panel LEDs                    | 1 LED shows if surge suppression is intact                        |
| SURGE / NOISE SUPPRESSION           |   |
| UPS AC Suppression Joule Rating     | 720 joules  |
| EMI / RFI AC Noise Suppression      | 20 dB   |
| PHYSICAL                            |   |
| Shipping Weight (lbs.)              | 12.00   |
| Shipping Weight (kg)                | 5.44  |
| Unit Dimensions (hwd / in.)         | 4 x 5 x 5.75  |
| Unit Dimensions (hwd / cm)          | 10.16 x 12.7 x 14.61  |
| Material of Construction            | Steel   |
| Form Factors Supported              | Short tower format with keyhole slots for wall-mount applications |
| WARRANTY                            |   |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|   |  |
|---|--|
| Product Warranty Period (Worldwide)                           | 2-year limited warranty                              |
| Connected Equipment Insurance<br>(U.S., Canada & Puerto Rico) | \$10,000 <a href="#">Ultimate Lifetime Insurance</a> |

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:  
<http://www.tripplite.com/products/product-certification-agencies>