

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Tripp Lite N022-250-GY

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>





Tripp Lite

1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Solid PVC Cable

MODEL NUMBER: N022-250-GY

Description

Tripp Lite's 250-ft. gray category 5e (Cat5e) solid PVC bulk cable is designed for premise (in-wall) cabling applications. This 24 AWG 4-pair solid cable has a PVC jacket and is rated for 350MHz/1Gbps communication. Used for all non-plenum horizontal wiring applications. Meets most current industry standards including IEEE 802.3ab, IEEE 802.5, ANSI/EIA/TIA 568, ISO/IEC11801 and ETL (category 5e draft 11). Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

Features

- Designed for premise(in-wall) cabling applications
- Cabling for category 5(Cat5) and 5e(Cat5e) applications
- Length: 250-ft. Color: gray
- 24 AWG 4-pair solid cable with PVC jacket
- Rated for 350MHz/ 1Gbps communication
- Meets most current industry standards including IEEE 802.3ab, IEEE 802.5, ANSI/EIA/TIA 568, ISO/IEC 11801 and ETL(category 5e draft 11)
- Available in other lengths
- Available in stranded copper cable(N020-01K-GY), in plenum cable(N024-01K) and in Cat6(N222-01K and N224-01K)
- · Warranted to be free from defects in materials and workmanship for life

Specifications

INPUT	
Cable Length (ft.)	250
Cable Length (m)	76.20

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies

Highlights

 Premium cabling for Category 5 and 5e applications — rated for 350 MHz/1Gbps communications

System Requirements

 For all non-Plenum horizontal premise (in-wall) wiring applications for Network Installations 1000 Base-T (1Gbps Ethernet), 10/100 Base-T (Ethernet), 100Mbps TPDDI, 155 Mbps ATM, ISDN, voice and Token Ring Type 3 applications.

Package Includes

250-ft. Cat5e Gray Bulk Patch
Cable Solid PVC 24AWG 350MHz