

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Tripp Lite P602-006-R

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



Distributor of Tripp Lite: Excellent Integrated System Limited Datasheet of P602-006-R - CABLE PARALLEL DB25M - CEN36M 6'

TRIPP-LITE

Tripp Lite

1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Computer Cable, 6-ft. Bi-Directional Parallel Printer Cen36M to DB25M

MODEL NUMBER: P602-006-R



Description

Tripp Lite's 6-ft. bi-directional parallel printer cable connects computers with a DB25 female parallel port to parallel printers with a Centronics 36 female parallel port. The cable has DB25 male/Cent36 male connectors

Highlights

- Superior molded cables with integral strain relief and foil-shielding for maximum EMI/RFI protection
- Provides superior conductivity and support for high-speed bi-directional printing
- Retail packaging

System Requirements

- Computers with a DB25 Female parallel port
- Parallel printers with a Centronics 36 Female parallel port with Bi-Directional communication (although not essential).

Package Includes

 6-ft. Bidir Parallel Cable Cen36M to DB25M

and supports bi-directional communication. It is manufactured from superior molded cable with integral strain relief and foil shielding for maximum EMI/RFI protection. Bi-directional communication allows your printer to broadcast printer error messages back to network computers. Use IEEE cable if IEEE specifications are required. Tripp Lite warrants this product to be free from defects in materials and workmanship for life. Clamshell retail package.

Features

- Supports bi-directional communication
- Length 6-ft. Connectors: DB25 male/Cent36 male
- Superior molded cable with integral strain relief and foil shielding for maximum EMI/RFI protection
- Bi-directional communication allows your printer to broadcast printer error messages back to network computers
- Molded ends with easy-grip textured overmold
- Use IEEE cable if IEEE specifications are required

Specifications

INPUT	
Cable Length (ft.)	6
Cable Length (m)	1.83
CONNECTIONS	
Side A - Connector 1	DB25 (MALE)





Tripp Lite Chicago, IL 60609 USA Telephone: 773.869.1234

Side B - Connector 1	CENTRONICS 36 (MALE)
WARRANTY	

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies