

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Tripp Lite SUPER6TEL12

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



Distributor of Tripp Lite: Excellent Integrated System Limited Datasheet of SUPER6TEL12 - SURGE SUPPR 7OUT 12'CORD W/RJ11



Tripp Lite

1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Protect It! 7-Outlet Surge Protector, 12-ft. Cord, 1080 Joules, Fax/Modem Protection, RJ11

MODEL NUMBER: SUPER6TEL12







Highlights

- 7 outlets / 12-ft. cord
- 1080 joule rating
- Modem/fax surge protection
- \$50,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

Package Includes

- SUPER6TEL12 Surge
 Suppressor
- 6-ft. telephone cord
- Instruction manual with warranty information

Description

Tripp Lite's SUPER6TEL12 surge suppressor offers complete AC and phone line surge suppression for comprehensive protection of workstations, desktop PCs, telecom systems and other sensitive electronics. High-grade AC surge suppression shields connected equipment from damage and performance problems due to transient surges. Set of RJ11 telephone line suppression jacks protect dialup and DSL modem lines, fax machines, cordless phones and more. SUPER6TEL12 offers 7 total outlets, 12 foot cord with a space-saving right-angle plug and diagnostic LEDs to warn of wiring problems and suppressor damage. Heavy grade AC suppression rated at 1080 joules shields equipment from surges and line noise. Attractive white suppressor housing with keyhole mounting tabs and 3 designated transformer plug outlets offers convenient protection of desktop computer equipment and accessories. \$50,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

PLUG/OUTLETS: Input: NEMA5-15P/Output: 7 NEMA5-15R/12-ft. AC line cord

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA5-15R wall receptacle)

FORMAT: Corded multi-outlet strip with 3 transformer spaced outlets

SUPPRESSION: AC: 150V RMS Clamping/1080 joules/330V UL1449 Let-through Rating Phone: Single telephone line surge suppression (RJ11 jacks, 2 wire, 1 line)

Features

- 1080 joules AC surge suppression shields equipment from the strongest surges and line noise
- 7 AC outlets with room for 3 transformer plugs without blocking outlets covers computers and all peripherals
- Phone line surge suppression protects both dialup and DSL modems, plus fax machines, cordless phones and more (pair of RJ11 jacks, 2 wire, 1 line, includes 6 ft phone cable)
- 12 foot cord with a space-saving right angle plug
- Built-in power switch and 15 amp circuit breaker offers power control and overload protection over all outlets
- Fail-safe thermal fusing protects against fire and other damage in the event of an extreme, extended overvoltage or surge condition
- Diagnostic LEDs confirm outlet grounding and surge suppression status
- UL1449 3rd Edition Rated (330V all modes), UL1363 (Power Tap), UL497A (Communications), Meets FCC part 68 rules, cUL (Canada)
- Exceeds IEEE 587 category A & B surge suppression specifications





Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234

- \$50,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)
- Automatic shutoff cuts power to outlets when the protection circuit has been compromised

Specifications

OUTPUT		
Frequency Compatibility	50 / 60 Hz	
Output Receptacles	(7) 5-15R	
Output (Watts)	1800	
Circuit Breaker (amps)	15	
Transformer Accommodation	Supports 3 large transformer plug accessories without covering remaining outlets, accepts up to 5 transformers total	
Outlet Orientation	Single row of 5, plus 2 side mounted outlets	
Right-Angle Outlets	No	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Connection Type	NEMA 5-15P	
Input Cord Length (ft.)	12	
Input Cord Length (m)	3.7	
Input Cord Gauge Type	14 gauge, SJT	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	72000	
Right-Angle Plug	Yes	
USER INTERFACE, ALERTS & CONTROLS		
Switches	Two position on/off power switch	
Diagnostic LED Details	Built-in LED confirms suppressor "protection present" (green) status	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	1080	
AC Suppression Response Time	< 1 ns	
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
Clamping Voltage (RMS)	150V	
UL1449 Let Through Rating	330V - UL Verified	
EMI / RFI Filtering	Up to 20 dB	





Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234

DATALINE SURGE SUPPRESSION Telephone/DSL Protection	Yes	
Telephone/DSL Protection Details	1 line	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		
Shipping Dimensions (hwd / in.)	12.4 x 7.09 x 1.77	
Shipping Dimensions (hwd / cm)	31.50 x 18.01 x 4.50	
Shipping Weight (lbs.)	1.98	
Shipping Weight (kg)	0.90	
Unit Dimensions (hwd / in.)	1.54 x 2.72 x 10.3	
Unit Dimensions (hwd / cm)	3.91 x 6.91 x 26.16	
Unit Weight (Ibs.)	1.82	
Unit Weight (kg)	0.83	
Material of Construction	Plastic	
Integrated Keyhole Mounting Tabs	Keyhole mounting tabs enable wall mounting	
Housing Color	Light Gray	
Receptacle Color	Light Gray	
Color (AC Line Cord)	Light Gray	
Outlets Measurement (Center to Center)	Between Standard Outlets = 29mm; Between Transformer Outlets = 48mm	
Keyhole Slot Mounting Measurement (Center to Center)	Distance between slots = 78mm; Distance between slot height = 24mm	
CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition	
UL1363 (Power Tap)	UL1363	
UL497A (Communications)	UL497A	
FCC Part 68 (Communications)	FCC Part 68	
cUL / CSA (Canada)	cUL	
Industry Canada (Communications)	Industry Canada	
Approvals	Exceeds IEEE 587 category A&B specifications	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	





Tripp Lite

1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Connected Equipment Insurance (U.S., Canada & Puerto Rico)

\$50,000 Ultimate Lifetime Insurance

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies