

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Johanson Technology Inc.](#)
[2450BP39E100AE](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

"PRELIMINARY"

2.45 GHz Band Pass Filter

P/N 2450BP39E100A

Detail Specification: 03/01/05

Page 1 of 2

General Specifications

Part Number	2450BP39E100A	
Frequency (MHz)	2400 - 2500	
Insertion Loss	2.6 dB max.	
Return Loss	8.9 dB min.	
Attenuation (min.)	880 ~ 915 MHz	42
Attenuation (min.)	1710 ~ 1990MHz	20
Attenuation (min.)	2110 ~ 2170MHz	8
Attenuation (min.)	2700MHz	20
Attenuation (min.)	4800 ~ 5000MHz	27
Attenuation (min.)	7200 ~ 7500MHz	15



Input Power	500 mW max.
Impedance	50 Ω
Operating Temperature	-40 to +85°C
Storage Temperature	-40 to +85°C
Reel Quantity	3,000

Terminal Configuration

No.	Function
1	GND
2	OUT
3	GND
4	IN

Mechanical Dimensions

	In	mm
L	0.098 $\pm$ 0.008	2.50 $\pm$ 0.20
W	0.079 $\pm$ 0.008	2.00 $\pm$ 0.20
T	0.043 $\pm$ 0.004	1.10 $\pm$ 0.10
a	0.012 $\pm$ 0.008	0.30 $\pm$ 0.20
b	0.024 $\pm$ 0.008	0.60 $\pm$ 0.20
c	0.012 $\pm$ 0.008	0.30 $\pm$ 0.20




Mounting Considerations

Mount these devices with brown mark facing up.

* Line width should be designed to provide 50 Ω impedance matching characteristics.

Units: mm



Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.

"PRELIMINARY"


2.45 GHz Band Pass Filter

P/N 2450BP39E100A

Detail Specification: 03/01/05

Page 2 of 2

Typical Electrical Performance (T=25°C)



Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.