

Excellent Integrated System Limited



Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:


[On-Shore Technology, Inc.](#)
[OSTTJ025153](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



N=Number of poles



THESE DRAWINGS AND SPECIFICATIONS
ARE THE PROPERTY OF ON-SHORE
TECHNOLOGY, INC. AND SHALL NOT BE
REPRODUCED, COPIED OR USED IN ANY
MANNER WITHOUT THE PRIOR WRITTEN
CONSENT OF ON-SHORE TECHNOLOGY,
INC.

SIGN	DATE	DESCRIPTION	APPROVER

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Terminal body
(metal housing): Brass(CuZn)
- Terminal screw: Steel Zinc plating "-" slot type
- Wire guard: PhBz ,Tin plated
- Insulator (housing): Thermoplastic (UL94V-0)

Electrical cULus / CSA/VDE / TUV

- Voltage rating: 300V/250V/300V/300V
- Current rating: 20A/15A/20A/20A
- Wire range: 2.5mm²/ 0.34-2.5mm²
- Solid wire(AWG): 12-24/14-22
- Stranded wire(AWG): 12-24/14-22
- Torque: 5Lb-In/5kgf.cm/0.5N.m/0.56N.m
- Screw: M3
- Wire strip length: 7-8mm
- Withstanding Voltage: 1.6KV/1.5KV/2.5KV/2.5KV
- Operating temperature: -30°C to +105°C
- Safety Approval: cULus CE TUV

RoHS Compliant

PART NUMBER:

OSTTJXX5153

No. of Poles
02 2 Poles
03 3 Poles
... ..
24 24 Poles

COLOR
0: Black
5: Green (Standard)
6: Blue
8: Grey



ON-SHORE TECHNOLOGY, INC.

TITLE	OSTTJ - 5.08mm Series						
PART NO.	OSTTJXX5153			DWG NO.	OSTTJXX5153.DWG		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance		
Shi Jun 2006.10.23	Marvin 2006.10.23	Marvin 2006.10.23	Marvin 2006.10.23			UNIT: mm	X ±0.50
						SCALE: NONE	X.X ±0.30
							X.XX ±0.10
					SHEET: 01/01	REV: E	X* ±1*