

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Diodes Incorporated](#)  
[BC846AS-7](#)

For any questions, you can email us directly:


[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

**Features**

- Ideally Suited for Automatic Insertion
- For Switching and AF Amplifier Applications
- Complementary PNP Type Available (BC856AS)
- **Lead Free/RoHS Compliant (Note 1)**
- **"Green" Device (Note 4 and 5)**

**Mechanical Data**

- Case: SOT-363
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminals: Solderable per MIL-STD-202, Method 208
- Lead Free Plating (Matte Tin Finish annealed over Alloy 42 leadframe).
- Terminal Connections: See Diagram
- Marking Information: See Page 3
- Ordering & Date Code Information: See Page 3
- Weight: 0.006 grams (approximate)



| SOT-363              |              |      |
|----------------------|--------------|------|
| Dim                  | Min          | Max  |
| A                    | 0.10         | 0.30 |
| B                    | 1.15         | 1.35 |
| C                    | 2.00         | 2.20 |
| D                    | 0.65 Nominal |      |
| F                    | 0.30         | 0.40 |
| H                    | 1.80         | 2.20 |
| J                    | —            | 0.10 |
| K                    | 0.90         | 1.00 |
| L                    | 0.25         | 0.40 |
| M                    | 0.10         | 0.25 |
| $\alpha$             | 0°           | 8°   |
| All Dimensions in mm |              |      |

**Maximum Ratings** @T<sub>A</sub> = 25°C unless otherwise specified

| Characteristic                                   | Symbol                            | Value       | Unit |
|--|-----------------------------------|-------------|------|
| Collector-Base Voltage                           | V <sub>CBO</sub>                  | 80          | V    |
| Collector-Emitter Voltage                        | V <sub>CEO</sub>                  | 65          | V    |
| Emitter-Base Voltage                             | V <sub>EBO</sub>                  | 6.0         | V    |
| Collector Current                                | I <sub>C</sub>                    | 100         | mA   |
| Peak Collector Current                           | I <sub>CM</sub>                   | 200         | mA   |
| Peak Emitter Current                             | I <sub>EM</sub>                   | 200         | mA   |
| Power Dissipation (Note 2)                       | P <sub>d</sub>                    | 200         | mW   |
| Thermal Resistance, Junction to Ambient (Note 2) | R <sub>θJA</sub>                  | 625         | °C/W |
| Operating and Storage Temperature Range          | T <sub>J</sub> , T <sub>stg</sub> | -65 to +150 | °C   |

**Electrical Characteristics** @T<sub>A</sub> = 25°C unless otherwise specified

| Characteristic                                | Symbol   | Min | Typ        | Max             | Unit           | Test Condition  |
|---|--|-----|------------|-----------------|----------------|---|
| Collector-Base Breakdown Voltage (Note 3)     | V <sub>(BR)CBO</sub>                                     | 80  | —          | —               | V              | I <sub>C</sub> = 10μA, I <sub>B</sub> = 0   |
| Collector-Emitter Breakdown Voltage (Note 3)  | V <sub>(BR)CEO</sub>                                     | 65  | —          | —               | V              | I <sub>C</sub> = 10mA, I <sub>B</sub> = 0   |
| Emitter-Base Breakdown Voltage (Note 3)       | V <sub>(BR)EBO</sub>                                     | 6   | —          | —               | V              | I <sub>E</sub> = 1μA, I <sub>C</sub> = 0  |
| DC Current Gain (Note 3)                      | h <sub>FE</sub>  | 110 | —          | 220             | —              | V <sub>CE</sub> = 5.0V, I <sub>C</sub> = 2.0mA  |
| Collector-Emitter Saturation Voltage (Note 3) | V <sub>CE(SAT)</sub>                                     | —   | 90<br>200  | 250<br>600      | mV             | I <sub>C</sub> = 10mA, I <sub>B</sub> = 0.5mA<br>I <sub>C</sub> = 100mA, I <sub>B</sub> = 5.0mA |
| Base-Emitter Saturation Voltage (Note 3)      | V <sub>BE(SAT)</sub>                                     | —   | 700<br>900 | —               | mV             | I <sub>C</sub> = 10mA, I <sub>B</sub> = 0.5mA<br>I <sub>C</sub> = 100mA, I <sub>B</sub> = 5.0mA |
| Base-Emitter Voltage (Note 3)                 | V <sub>BE(ON)</sub>                                      | 580 | 660        | 700<br>770      | mV             | V <sub>CE</sub> = 5.0V, I <sub>C</sub> = 2.0mA<br>V <sub>CE</sub> = 5.0V, I <sub>C</sub> = 10mA |
| Collector-Cutoff Current (Note 3)             | I <sub>CES</sub><br>I <sub>CBO</sub><br>I <sub>CBO</sub> | —   | —          | 15<br>15<br>5.0 | nA<br>nA<br>μA | V <sub>CE</sub> = 80V<br>V <sub>CB</sub> = 40V<br>V <sub>CB</sub> = 30V, T <sub>A</sub> = 150°C |
| Gain Bandwidth Product                        | f <sub>T</sub>   | 100 | —          | —               | MHz            | V <sub>CE</sub> = 5.0V, I <sub>C</sub> = 10mA,<br>f = 100MHz                                    |
| Collector-Base Capacitance                    | C <sub>CB</sub>  | —   | 2.0        | —               | pF             | V <sub>CB</sub> = 10V, f = 1.0MHz   |

- Notes:
1. No purposefully added lead.
  2. Device mounted on FR-4 PCB, pad layout as shown on page 3 or on Diodes Inc. suggested pad layout document AP02001, which can be found on our website at <http://www.diodes.com/datasheets/ap02001.pdf>.
  3. Short duration pulse test used to minimize self-heating effect.
  4. Diodes Inc.'s "Green" policy can be found on our website at [http://www.diodes.com/products/lead\\_free/index.php](http://www.diodes.com/products/lead_free/index.php).
  5. Product manufactured with Date Code UO (week 40, 2007) and newer are built with Green Molding Compound. Product manufactured prior to Date Code UO are built with Non-Green Molding Compound and may contain Halogens or Sb2O3 Fire Retardants.



NEW PRODUCT




Fig. 1 Power Derating Curve (Note 2)




Fig. 2 Typical Collector Current vs. Collector Emitter Voltage




Fig. 3 Typical DC Current Gain vs. Collector Current




Fig. 4 Typical Collector Emitter Saturation Voltage vs. Collector Current




Fig. 5 Typical Base Emitter Turn-On Voltage vs. Collector Current




Fig. 6 Typical Base Emitter Saturation Voltage vs. Collector Current



NEW PRODUCT




Fig. 7 Typical Capacitance Characteristics





Fig. 8 Typical Gain-Bandwidth Product vs. Collector Current

**Ordering Information** (Note 6)

| Device    | Packaging | Shipping         |
|-----------|-----------|------------------|
| BC846AS-7 | SOT-363   | 3000/Tape & Reel |

Notes: 6. For packaging details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

**Marking Information**



KNS = Product Type Marking Code  
 YM = Date Code Marking  
 Y = Year ex: U = 2007  
 M = Month ex: 9 = September

Data Code Key

| Year | 2007 | 2008 | 2009 | 2010 | 2011 | 2012 |
|------|------|------|------|------|------|------|
| Code | U    | V    | W    | X    | Y    | Z    |

| Month | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Code  | 1   | 2   | 3   | 4   | 5   | 6   | 7   | 8   | 9   | O   | N   | D   |

**IMPORTANT NOTICE**

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

**LIFE SUPPORT**

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.