

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[CUI Inc.](#)
[CLS0361-L152](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



CUI INC

Part No: CLS0361-L152

Description: speaker

Date: 7/03/2007

Unit: mm


Page No: 1 of 2

Specifications

Nominal Size	36 mm
Impedance	8 Ohm $\pm$ 15% at 1 KHz 1 V
Resonant frequency	360 Hz $\pm$ 72 Hz at 1 V
Sound pressure level	88 dB/w $\pm$ 3 dB 1 w 50 cm ave. at 0.5K, 0.6K, 0.8K, 1K Hz
Response	Fo Hz ~ 20 KHz max 10 dB
Input power	Nominal 2 W Handling capacity 3 W
Operation	must be normal at program source 2 W
Buzz, rattle, etc.	must be normal at sine wave 4 V
Magnet	Size: 12.5 x 1.5 mm
Load test	White noise 2 W for 24 hours
Heat test	65 $\pm$ 2° C 20-50% R.H. 24 hours
Humidity test	40 $\pm$ 2° C 90-95% R.H. 24 hours




Frequency Response Curve

Potentiometer range	50 dB
Rectifier	RMS
Lower limit frequency	20 Hz
Wr. speed	100 mm/sec



Zero level 60 dB

REV.	DESCRIPTION	DATE
A	NEW DRAWING	7/3/2007



SPECIFICATIONS:
 WIRE: UL1007, #28AWG
 LENGTH: 152mm
 TOLERANCE:
 ±0.5mm UNLESS OTHERWISE
 SPECIFIED



CUI INC

20050 SW 112th Ave.
 Tualatin, OR 97062
 Phone: 503-612-2300
 800-275-4899
 Fax: 503-612-2383
 Website: www.cui.com

TITLE: LOW PROFILE SPEAKER	REV: A
PART NO. CLS0361-L152	UNITS: MM [INCHES]
DRAWN BY: ZRJ	APPROVED BY:
	SCALE: 2:1