

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Wurth Electronics Inc](#)
[744775015A](#)

For any questions, you can email us directly:

sales@integrated-circuit.com


Spezifikation für Freigabe / specification for release

Kunde / customer: _____
 Artikelnummer / part number: **744775015A**
 Bezeichnung : **SPEICHERDROSSEL WE-PD2**
 description : **POWER-CHOKE WE-PD2**



DATUM / DATE : 2004-10-11

A Mechanische Abmessungen / dimensions




marking dot is start winding
& inductance code

Typ L		
A	7,5 ± 0,3	mm
B	5,0 ± 0,3	mm
C	2,6 ref	mm
D	8,0 ref	mm
E	7,8 ref	mm
F	2,4 ref	mm

B Elektrische Eigenschaften / electrical properties:

Eigenschaften / properties	Testbedingungen / test conditions		Wert / value	Einheit / unit	tol.
Induktivität / inductance	1 kHz	L	1,50	μH	± 20%
Güte Q / Q factor	7,960 MHz	Q	32		
DC-Widerstand / DC-resistance		R _{DC}	0,02	Ω	max.
Nennstrom / rated current		I _{DC}	6,00	A	max.
Eigenres.-Frequenz / self-res.-frequency		SRF	120,00	MHZ	

C Lötpad / soldering spec.:



D Prüfgeräte / test equipment:

HP 4274 A für/for L und/and Q
HP 4274 A für/for R_{DC} und I_{DC}

E Testbedingungen / test conditions:

Luftfeuchtigkeit / humidity: 33%
 Umgebungstemperatur / temperature: +20°C

F Werkstoffe & Zulassungen / material & approvals:

Basismaterial / base material: Ferrit
 Draht / wire: class F

G Eigenschaften / general specifications:

Lagertemperatur / storage temperature: -40°C ~ + 125°C
 Betriebstemp. / operating temperature: -40°C ~ + 125°C

Freigabe erteilt / general release:	Kunde / customer			
.....			
Datum / date	Unterschrift / signature			
	Würth Elektronik	RT	Version 3	2004-10-11
		SST	Version 2	2003-07-02
		JH	Version 1	2000-12-06
Geprüft / checked	Kontrolliert / approved	Name	Änderung / modification	Datum / date

This electronic component is designed and developed with the intention for use in general electronics equipments. Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body. In addition, even electronic component in general electronic equipments when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before use. It is essential give consideration when to install a protective circuit at the design stage.

Würth Elektronik eiSos GmbH & Co.KG