

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[IXYS Corporation](#)
[VCC2X105-08IO7](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

VCC 2x105



Thyristor Modules

ECO-PAC 2

$I_{TRMS} = 2 \times 180A$
 $I_{TAVM} = 2 \times 105A$
 $V_{RRM} = 800-1800 V$

Preliminary Data

V_{RSM} V_{DSM} V	V_{RRM} V_{DRM} V	Typ
900	800	VCC 2x105 - 08i07
1300	1200	VCC 2x105 - 12i07
1500	1400	VCC 2x105 - 14i07
1700	1600	VCC 2x105 - 16i07
1900	1800	VCC 2x105 - 18i07



Symbol	Conditions	Maximum Ratings	
I_{TRMS}		180	A
I_{TAVM}	$T_C = 85^\circ C$; 180° sine	105	A
I_{TSM}	$T_{VJ} = 45^\circ C$; $V_R = 0 V$;	$t = 10 \text{ ms}$ (50 Hz), sine	2250 A
		$t = 8.3 \text{ ms}$ (60 Hz), sine	2400 A
I^2dt	$T_{VJ} = 45^\circ C$; $V_R = 0 V$;	$t = 10 \text{ ms}$ (50 Hz), sine	25300 A ² s
		$t = 8.3 \text{ ms}$ (60 Hz), sine	23900 A ² s
$(di/dt)_{cr}$	$T_{VJ} = 125^\circ C$; $f = 50 \text{ Hz}$; $t_p = 200 \mu s$; $V_D = 2/3 V_{DRM}$; $I_G = 0.45 A$; $di_G/dt = 0.45 A/\mu s$;	repetitive, $I_T = 250 A$	150 A/ μs
		non repetitive, $I_T = I_{TAVM}$	500 A/ μs
$(dv/dt)_{cr}$	$T_{VJ} = 125^\circ C$; $V_{DR} = 2/3 V_{DRM}$ $R_{GK} = \infty$, method 1 (linear voltage rise)	1000	V/ μs
P_{GM}	$T_{VJ} = 125^\circ C$; $I_T = I_{TAVM}$;	$t_p = 30 \text{ ms}$	≤ 10 W
		$t_p = 300 \text{ ms}$	≤ 5 W
P_{GAVM}		0.5	W
V_{RGM}		10	V
T_{VJ}		-40 ... + 125	°C
T_{VJM}		125	°C
T_{stg}		-40 ... + 125	°C
V_{ISOL}	50/60 Hz, RMS $I_{ISOL} \leq 1 \text{ mA}$	$t = 1 \text{ min}$	3000 V ~
		$t = 1 \text{ s}$	3600 V ~
M_d	Mounting torque (M4)	1.5 - 2.0	Nm
		14 - 18	lb.in.
Weight	typ.	26	g

Features

- Isolation voltage 3600 V~
- Planar glass passivated chips
- Low forward voltage drop
- Leads suitable for PC board soldering

Applications

- DC motor control
- Light and temperature control
- Softstart AC motor controller
- Solid state switches

Advantages

- Easy to mount with two screws
- Space and weight savings
- Improved temperature and power cycling
- High power density
- Small and light weight

Data according to IEC 60747 refer to a single thyristor unless otherwise stated

IXYS reserves the right to change limits, test conditions and dimensions.

Component				
Symbol	Conditions	Characteristic Values		
		min.	typ.	max.
I_D, I_R	$T_{VJ} = 125^\circ\text{C}; V_R = V_{RRM}; V_D = V_{DRM}$			5 mA
V_T	$I_T = 300 \text{ A}; T_{VJ} = 25^\circ\text{C}$			1.5 V
V_{TO}	For power-loss calculations only			0.8 V
r_T				2.4 mΩ
V_{GT}	$V_D = 6 \text{ V}; T_{VJ} = 25^\circ\text{C}$ $T_{VJ} = -40^\circ\text{C}$			1.5 V 1.6 V
I_{GT}	$V_D = 6 \text{ V}; T_{VJ} = 25^\circ\text{C}$ $T_{VJ} = -40^\circ\text{C}$			150 mA 200 mA
V_{GD}	$T_{VJ} = 125^\circ\text{C}; V_D = \frac{2}{3}V_{DRM}$			0.2 V
I_{GD}	$T_{VJ} = 125^\circ\text{C}; V_D = \frac{2}{3}V_{DRM}$			10 mA
I_L	$T_{VJ} = 25^\circ\text{C}; t_p = 10 \text{ ms}$ $I_G = 0.45 \text{ A}; di_G/dt = 0.45 \text{ A}/\mu\text{s}$			450 mA
I_H	$T_{VJ} = 25^\circ\text{C}; V_D = 6 \text{ V}; R_{GK} = \infty$			200 mA
t_{gd}	$T_{VJ} = 25^\circ\text{C}; V_D = \frac{1}{2} V_{DRM}$ $I_G = 0.45 \text{ A}; di_G/dt = 0.45 \text{ A}/\mu\text{s}$			2 μs
R_{thJC}	per Thyristor; DC per module			0.26 K/W 0.13 K/W
R_{thCH}	per Thyristor; DC per module		0,2 0,1	K/W K/W
d_s	Creeping distance on surface			11.2 mm
d_A	Creeping distance in air			5.0 mm
a	Max. allowable acceleration			50 m/s ²

