

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Rohm Semiconductor](#)

[RRS110N03TB1](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

RRS110N03

Transistor

4V Drive Nch MOSFET

RRS110N03

●Structure

Silicon N-channel MOSFET

●Features

- 1) Low on-resistance.
- 2) Built-in G-S Protection Diode.
- 3) Small Surface Mount Package (SOP8).


●Applications

Switching


●Packaging specifications

Type	Package	Taping
	Code	TB
	Basic ordering unit (pieces)	2500
RRS110N03		○

●Dimensions (Unit : mm)



●Equivalent circuit



*A protection diode is included between the gate and the source terminals to protect the diode against static electricity when the product is in use. Use the protection circuit when the fixed voltages are exceeded.

●Absolute maximum ratings (Ta=25°C)

Parameter	Symbol	Limits	Unit
Drain-source voltage	V_{DS}	30	V
Gate-source voltage	V_{GS}	± 20	V
Drain current	Continuous	I_D	± 11 A
	Pulsed	I_{DP} *1	± 44 A
Source current (Body diode)	Continuous	I_S	1.6 A
	Pulsed	I_{SP} *1	44 A
Total power dissipation	P_D *2	2.0	W
Channel temperature	T_{ch}	150	°C
Range of storage temperature	T_{stg}	-55 to +150	°C

*1 $P_w \leq 10\mu s$, Duty cycle $\leq 1\%$

*2 Mounted on a ceramic board.

●Thermal resistance

Parameter	Symbol	Limits	Unit
Channel to ambient	$R_{th}(ch-a)$ *	62.5	°C / W

* Mounted on a ceramic board.

RRS110N03

Transistor

●Electrical characteristics (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Gate-source leakage	I_{GSS}	—	—	± 10	μA	$V_{GS}=\pm 20V, V_{DS}=0V$
Drain-source breakdown voltage	$V_{(BR) DSS}$	30	—	—	V	$I_D=1mA, V_{GS}=0V$
Zero gate voltage drain current	I_{DSS}	—	—	1	μA	$V_{DS}=30V, V_{GS}=0V$
Gate threshold voltage	$V_{GS(th)}$	1.0	—	2.5	V	$V_{DS}=10V, I_D=1mA$
Static drain-source on-starte resistance	$R_{DS(on)}$ *	—	9.0	12.6	m Ω	$I_D=11A, V_{GS}=10V$
		—	11.0	15.4		$I_D=11A, V_{GS}=4.5V$
		—	11.5	16.0		$I_D=11A, V_{GS}=4V$
Forward transfer admittance	$ Y_{fs} $ *	10	—	—	S	$I_D=11A, V_{DS}=10V$
Input capacitance	C_{iss}	—	2000	—	pF	$V_{DS}=10V$
Output capacitance	C_{oss}	—	330	—	pF	$V_{GS}=0V$
Reverse transfer capacitance	C_{rss}	—	280	—	pF	$f=1MHz$
Turn-on delay time	$t_{d(on)}$ *	—	16	—	ns	$I_D=5.5A, V_{DD} \div 15V$
Rise time	t_r *	—	60	—	ns	$V_{GS}=10V$
Turn-off delay time	$t_{d(off)}$ *	—	80	—	ns	$R_L=2.73\Omega$
Fall time	t_f *	—	100	—	ns	$R_G=10\Omega$
Total gate charge	Q_g *	—	22.0	33.0	nC	$I_D=11A, V_{DD} \div 15V$
Gate-source charge	Q_{gs} *	—	5.5	—	nC	$V_{GS}=5V$
Gate-drain charge	Q_{gd} *	—	7.5	—	nC	$R_L=1.36\Omega, R_G=10\Omega$

*Pulsed

●Body diode characteristics (Source-Drain) (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Forward voltage	V_{SD} *	—	—	1.2	V	$I_S=11A, V_{GS}=0V$

*Pulsed

RRS110N03

Transistor

●Electrical characteristic curves




Fig.1 Typical Transfer Characteristics




Fig.2 Static Drain-Source On-State Resistance vs. Drain Current(I)




Fig.3 Static Drain-Source On-State Resistance vs. Drain Current(II)




Fig.4 Static Drain-Source On-State Resistance vs. Drain Current(III)




Fig.5 Static Drain-Source On-State Resistance vs. Drain Current(IV)




Fig.6 Static Drain-Source On-State Resistance vs. Gate-Source Voltage




Fig.7 Forward Transfer Admittance vs. Drain Current




Fig.8 Typical Capacitance vs. Drain-Source Voltage




Fig.9 Switching Characteristics

RRS110N03

Transistor




Fig.10 Dynamic Input Characteristics




Fig.11 Source Current vs. Source-Drain Voltage

●Measurement circuit




Fig.12 Switching Time Test Circuit




Fig.13 Switching Time Waveforms




Fig.14 Gate Charge Test Circuit




Fig.15 Gate Charge Waveform

Appendix

Notes

- No technical content pages of this document may be reproduced in any form or transmitted by any means without prior permission of ROHM CO.,LTD.
- The contents described herein are subject to change without notice. The specifications for the product described in this document are for reference only. Upon actual use, therefore, please request that specifications to be separately delivered.
- Application circuit diagrams and circuit constants contained herein are shown as examples of standard use and operation. Please pay careful attention to the peripheral conditions when designing circuits and deciding upon circuit constants in the set.
- Any data, including, but not limited to application circuit diagrams information, described herein are intended only as illustrations of such devices and not as the specifications for such devices. ROHM CO.,LTD. disclaims any warranty that any use of such devices shall be free from infringement of any third party's intellectual property rights or other proprietary rights, and further, assumes no liability of whatsoever nature in the event of any such infringement, or arising from or connected with or related to the use of such devices.
- Upon the sale of any such devices, other than for buyer's right to use such devices itself, resell or otherwise dispose of the same, no express or implied right or license to practice or commercially exploit any intellectual property rights or other proprietary rights owned or controlled by
- ROHM CO., LTD. is granted to any such buyer.
- Products listed in this document are no antiradiation design.

The products listed in this document are designed to be used with ordinary electronic equipment or devices (such as audio visual equipment, office-automation equipment, communications devices, electrical appliances and electronic toys).

Should you intend to use these products with equipment or devices which require an extremely high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), please be sure to consult with our sales representative in advance.

It is our top priority to supply products with the utmost quality and reliability. However, there is always a chance of failure due to unexpected factors. Therefore, please take into account the derating characteristics and allow for sufficient safety features, such as extra margin, anti-flammability, and fail-safe measures when designing in order to prevent possible accidents that may result in bodily harm or fire caused by component failure. ROHM cannot be held responsible for any damages arising from the use of the products under conditions out of the range of the specifications or due to non-compliance with the NOTES specified in this catalog.

Thank you for your accessing to ROHM product informations.

More detail product informations and catalogs are available, please contact your nearest sales office.

ROHM Customer Support System

THE AMERICAS / EUROPE / ASIA / JAPAN

www.rohm.com

Contact us : webmaster@rohm.co.jp