

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:


[E-Switch](#)
[100SP1T8B13M1REH](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

SHEET 1 OF 1

SWITCH FUNCTION		
POS. 1	POS. 2	POS. 3
ON	OFF	ON
2-3	OPEN	2-1



NOTE:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERMINAL NUMBERS FOR REF ONLY
- ▲ 4. PLATING MATERIAL: GOLD
5. RATING: 0.4 (VA) MAX @20V MAX
6. ELECTRIC LIFE: 40,000 MAKE-AND-BREAK CYCLES AT FULL LOAD.
7. INSULATION RESISTANCE: 1,000 MΩ MIN.
8. DIELECTRIC STRENGTH: 1,000 V RMS @SEA LEVEL.
9. OPERATING TEMP.: -30°C to 85°C
- ▲ 10. HARDWARE TO BE SHIPPED BULK
T100004 - HEXNUT - QTY 2
T100012 - LOCKWASHER - QTY 1
T100003 - LOCKRING - QTY 1
11. ▲ DENOTES CRITICAL PARAMETER.

100SP1T8B13M1RE
(T111128)

15/32-32 UNS-2A
THREADS

E-SWITCH
MARKING ON
OPPOSITE SIDE

EPOXY SEAL

1 2 3
.76
[.030 in]
4.70
[.185 in]

3.96
[.156 in]

8.89
[.350 in]

11.38
[.448 in]

17.56
[.691 in]

6.09
[.240 in]

1.65
[.065 in]

.79
[.031 in]

KEYWAY

12.70
[.500 in]

6.86
[.270 in]

1.19
[.047 in]

2.03
[.080 in]

1.98
[.078 in]

.51
[.020 in]

3

2

1

ON OFF ON

ISOMETRIC

E-SWITCH®				
TITLE 100SP1T8B13M1REH				
SCALE 2:1	DATE 5/18/2005	DR JB	DWG ST111128	REV B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED