

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[E-Switch](#)

[KC15A10.001NPS](#)


For any questions, you can email us directly:

sales@integrated-circuit.com


SHEET 1 OF 1

NOTES:


1. ALL DIMENSION IN MM [INCH]
2. GENERAL TOLERANCE: $X.X = \pm 0.4$
 $X.XX = \pm 0.25$
3. TERM. NOS. FOR REF. ONLY
4. CONTACT RATING SWITCHING: 150mA, 250V AC/DC
350mA, 110V AC/DC
5. CONTACT RATING (NON-SWITCHING) 5A
6. CONTACT MATERIAL:
STANDARD SILVER over COPPER ALLOY
7. OPERATING FORCE: 425 ± 100 CM/STANDARD
8. OPERATING TEMP: -30° to 85°C
9. CIRCUIT SP: 5 POSITIONS, 30° INDEX,
10. DIELECTRIC STRENGTH 1000V RMS min. @ SEA LEVEL
11. HARDWARE SUPPLIED ON SWITCH- SEE BELOW
STOP RING, LOCKWASHER, & HEXNUT
12. ▲ DENOTES CRITICAL PARAMETER.




CONTACT CONFIGURATION
 Timing: NON-SHORTING (BBM)



RECOMMENDED P.C.B. LAYOUT



HARDWARE SUPPLIED
 ON SWITCH



REV.				TITLE			
A	13148	RELEASED FOR PRODUCTION	5/22/03	AR	KC15A10.001NPS		
REV.	ECN NO.	DESCRIPTION	DATE	CHKD	SCALE	DATE	DR
					1.5:1	5/22/03	AR
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED					DWG	G527542	REV
							A