

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[3M](#)  
[9755-CLEAR-1](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



# 9755 Transfer Adhesive Tape

## Medium Firm Pressure Sensitive, Acrylic Adhesive

### Data Sheet

- High adhesion to a variety of surfaces
- Supplied on 3 inch cores
- Widths from 1/2" to 54"

Like all 3M insulating tapes, 3M™ 9755 Transfer Adhesive is available in standard and custom widths and lengths. Standard length is 60 yards. Longer lengths, up to several times standard length, are available depending upon width. Check with Customer Service. 3M 9755 Transfer Adhesive is used for joining a wide variety of similar and dissimilar materials where high bond strength, high temperature, performance and excellent UV resistance are required.

| Properties                                 | Typical Values               |
|--|------------------------------|
| Adhesive                                   | A 35 Medium Firm Acrylic     |
| Release Liner                              | Moisture-Resistant Tan Paper |
| Adhesive Thickness                         | 5.0 mils/.13mm               |
| Release Liner Approximate Thickness        | 4.0 mils/.10mm               |
| Color                                      | Clear                        |
| Temperature Class Long Term-Days/Weeks     | 149°C/300°F                  |
| Temperature Class Short Term-Minutes/Hours | 232°C/450°F                  |
| UV Resistance                              | Excellent                    |
| Relative Solvent Resistance                | Very Good                    |

\*Not recommended for specification purposes. Product specifications will be provided upon request.

3M is a trademark of 3M.

#### **Important Notice**

All statements, technical information and recommendations related to the Seller's products are based on information believed to be reliable, but the accuracy or completeness thereof is not guaranteed. Before utilizing the product, the user should determine the suitability of the product for its intended use. The user assumes all risks and liability whatsoever in connection with such use.

Any statements or recommendations of the Seller which are not contained in the Seller's current publications shall have no force or effect unless contained in an agreement signed by an authorized officer of the Seller. The statements contained

herein are made in lieu of all warranties, expressed or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose which warranties are hereby expressly disclaimed.

SELLER SHALL NOT BE LIABLE TO THE USER OR ANY OTHER PERSON UNDER ANY LEGAL THEORY, INCLUDING BUT NOT LIMITED TO NEGLIGENCE OR STRICT LIABILITY, FOR ANY INJURY OR FOR ANY DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES SUSTAINED OR INCURRED BY REASON OF THE USE OF ANY OF THE SELLER'S PRODUCTS THAT WERE DEFECTIVE.

# **3M**

#### **Electrical Products Division**

6801 River Place Blvd.  
Austin, TX 78726-9000  
800 67 6 8381  
<http://www.3m.com/elpd>