

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Ametherm](#)
[SL03 10001](#)

For any questions, you can email us directly:


sales@integrated-circuit.com



ISO9001:2008 Certified

Mechanical Specifications (mm)

D:	3.0	± max
T:	3.0	± max
Lead Diameter	0.5	± nom
S:	2.5	± nom
L:	38.0	± nom
Coating Lead Run Down (straight Leads)		±
B:	3.00	± nom
C:	1.20	± nom



Electrical Specifications

Resistance:	10.0 Ω	± 20 %
Max Steady State Current upto 65°C:	1.00	A
Max Rec. Energy Rating:	2	J
Actual Failure Instantaneous Energy:	7	J
Maximum Capacitance @ 120 VAC:	100	μ f
Resistance @ 100% Max Current:	0.80	Ω
Resistance @ 50% Max Current:	2.00	Ω
Body Temperature at 100% Max Current:	112.80	°C
Dissipation Constant:	6.2	mw/°C
Thermal Time Constant:	52	Sec.
Material Type (for Beta and Curve):	A	

SL03 10001

Date: 11/11/2008	Drawn by: Erin Landis
Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Mehdi Samii
	Revision: A